according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Cartechnic Multi-Füller 2K
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Filler
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Auto-Teile-Ring GmbH

Marie-Curie-Str. 3

73770 Denkendorf

Deutschland / Germany

Telefon: +49 (0)711 918979-0

info@cartechnic.de www.cartechnic.de

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz - Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P242 Use non-sparking tools.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Store in a well-ventilated place. Keep cool.

· Additional information:

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

· 2.3 Other hazards

P403+P235

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)

Revision: 12.01.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

· vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	<15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.1-<0.25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 *Version number 5 (replaces version 4)* Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 2)

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

No special precautions are necessary if used correctly.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Ingredients with limit values that require monitoring at the workplace:		
123-86-4 n-Butyl acetate		
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm		
1330-20-7 Xylene		
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV		

Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m³, 125 ppm
	Long-term value: 441 mg/m³, 100 ppm
	Sk

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 3)

77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³

as Sn: Sk

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.
- · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 124-128 °C (123-86-4 n-Butyl acetate)
Flammability Flammable.

· Flammability · Lower and upper explosion limit

• **Lower:** 1.2 Vol % (123-86-4 n-Butyl acetate)

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 4) 7.5 Vol % (123-86-4 n-Butyl acetate) · Upper: · Flash point: 24 °C (DIN EN ISO 1523:2002) · Ignition temperature: >350 °C (DIN 51794) · Decomposition temperature: Not determined. Not determined. $\cdot pH$ · Viscosity: · Kinematic viscosity at 20 °C >60 s (ISO 6 mm) · Dynamic: Not determined. ·Solubility Not miscible or difficult to mix. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: <15 hPa (Hydroxy acrylic resin) · Density and/or relative density · Density at 20 °C: 1.593 g/cm³ (DIN EN ISO 2811-1) · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information · Appearance: · Form: Fluid Important information on protection of health and environment, and on safety. Product is not selfigniting. · Auto-ignition temperature: Product is not explosive. However, formation of · Explosive properties: explosive air/vapour mixtures are possible. · Solvent content: 23.41 % · VOC (EC) 76.3 % · Solids content (weight-%): · Change in condition Not determined. · Evaporation rate · Information with regard to physical hazard classes Void · Explosives · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void · Flammable liquids Flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

· Endocrine disrupting properties	
540-97-6 Dodecamethylcyclohexasiloxane	List II
541-02-6 Decamethylcyclopentasiloxane	List II
556-67-2 octamethylcyclotetrasiloxane	List II, III

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	UNI 263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
	2 (EL) EL . LL 1: -1
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	30 E E S E
Stowage Category	F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according to IM	70
instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 D/E
Remarks:	$\leq 450 \ l$: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 30 l: 2.2.3.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT, 3, III

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 5 (replaces version 4) Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 12.01.2023 Revision: 12.01.2023

Trade name: Cartechnic Multi-Füller 2K

```
(Contd. of page 8)
 Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation - Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 2: Germ cell mutagenicity – Category 2
 Repr. 1B: Reproductive toxicity - Category 1B
 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard - Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
* Data compared to the previous version altered.
```