

according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VELIND Rostlöser mit MOS2 300ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive Care (spray, liquid)

Uses advised against

No information available. Use(Usage) exclusively according to labelled intended purpose!

1.3. Details of the supplier of the safety data sheet

Company name: VELIND Aerosol GmbH
Street: Passower Chaussee 111
Place: D-16303 Schwedt/O

Telephone: +49 33 32 / 4 50 88 - 0 Telefax: +49 33 32 / 4 50 88 - 30

e-mail: info@velind.de

Contact person: Witt Telephone: 18

e-mail: qs@velind.de Internet: www.velind.de

Responsible Department: QS

1.4. Emergency telephone GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und

number: Thüringen: +49 3 61 / 7 30 73 -0

Further Information

Emergency - Phonecalls to +49 (0) 33 32 / 4 50 88 16 (during office-hours from 8.00 a.m. to 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 2 of 12

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of the Contents/container of waste according to with local/national regulations

applicable legislation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding

50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of

ignition - No smoking. Keep out of the reach of children.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P102-P103-P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aerosol

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification	•	•			
64742-48-9	Naphtha (Erdöl), mit Wasserstoff behandelt, schwer					
	918-481-9	649-327-00-6	01-2119457273-39			
	Asp. Tox. 1; H304 EUH066					
111-76-2	2-butoxyethanol		1 - < 5 %			
	203-905-0	603-014-00-0	01-2119475108-36			
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 3 of 12

After inhalation

Provide fresh air

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Not applicable, because aerosol. If it does, consult a doctor immediately and show him box or label.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur::

Intoxication. unconsciousness. Headache. drowsiness. Dizziness. Depression of the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam. Water spray. dry extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Contains gas under pressure; may explode if heated. (H280) Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide Carbon dioxide.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Remove according to the regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Provide adequate ventilation. Wear personal protection equipment. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area. Collect in closed containers for disposal.



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 4 of 12

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Keep away from hot surfaces. Read label before use. Observe in addition any national regulations!

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Maximum storage temperature: 30°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Keep away from: Oxidizing agents. strong alkalis.

Further information on storage conditions

Fire class: C

7.3. Specific end use(s)

Automotive Care (spray, liquid)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246	ĺ	STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	I	Post shift



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 5 of 12

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
111-76-2	2-butoxyethanol			
Worker DNEL,	acute	dermal	systemic	89 mg/kg bw/day
Worker DNEL,	acute	inhalation	systemic	663 mg/m³
Worker DNEL,	acute	inhalation	local	246 mg/m³
Worker DNEL,	long-term	dermal	systemic	75 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	98 mg/m³
Consumer DNEL, acute		dermal	systemic	44,5 mg/kg bw/day
Consumer DNE	EL, acute	inhalation	systemic	426 mg/m³
Consumer DNEL, acute		oral	systemic	13,4 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	123 mg/m³
Consumer DNEL, long-term		dermal	systemic	38 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	49 mg/m³
Consumer DNE	EL, long-term	oral	systemic	3,2 mg/kg bw/day

PNEC values

CAS No	Substance				
Environment	Environmental compartment				
111-76-2	2-butoxyethanol				
Freshwater		8,8 mg/l			
Marine water		0,88 mg/l			
Freshwater sediment		34,6 mg/kg			
Marine sediment		3,46 mg/kg			
Micro-organisms in sewage treatment plants (STP)		463 mg/l			
Soil	2,8 mg/kg				

8.2. Exposure controls









Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Exposure controls / Personal protection equipment

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Product code: 31019 Revision date: 27.02.2019 Page 6 of 12

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber). Butyl rubber.

Thickness of glove material: 0,7mm

Breakthrough times and swelling properties of the material must be taken into consideration.

Protect skin by using skin protective cream. Set out skin protection guidelines.

Apply skin care products after work.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing . . .

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol Active component: liquid

Colour: black

Odour: characteristic

not determined pH-Value:

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: not determined

Flash point: > 60 (Active component) °C

Flammability

Solid: not applicable Gas: not applicable

Explosive properties

not explosive. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 0,5 vol. % Upper explosion limits: 9,4 vol. % not determined Ignition temperature:

Auto-ignition temperature

Solid: not applicable Gas: not applicable not determined Decomposition temperature:

Oxidizing properties

Not oxidising.

not determined Vapour pressure: Density: 0,83 (Active component) g/cm3 Bulk density:

not applicable

Print date: 27.02.2019

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 7 of 12

Partition coefficient:

Viscosity / dynamic:

vapour density:

not determined

not determined

not determined

not determined

not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. The product has not been tested.

10.2. Chemical stability

Stable with proper storage and handling.

10.3. Possibility of hazardous reactions

No decomposition if used as intended

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Do not spray on naked flames or any incandescent material.

Heating causes rise in pressure with risk of bursting. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

10.6. Hazardous decomposition products

Refer to chapter 5.

No decomposition if used as intended

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

Mixture not tested. There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 8 of 12

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Naphtha (Erdöl), mit Was	Naphtha (Erdöl), mit Wasserstoff behandelt, schwer				
	oral	LD50 mg/kg	>2000	Rat		OECD 401
	dermal	LD50 mg/kg	>2000	Rabbit		OECD 402
111-76-2	2-butoxyethanol					
	oral	LD50 mg/kg	>2000	Rat		
	dermal	LD50 mg/kg	>2000	Guinea-pig.		
	inhalation vapour	ATE	11 mg/l			
	inhalation aerosol	ATE	1,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Sensitising effects

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

There are no data available on the mixture itself. No data available

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself. No data available

Practical experience

Observations relevant to classification

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

Further information

Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Mixture not tested. There are no data available on the preparation/mixture itself.



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 9 of 12

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-48-9	Naphtha (Erdöl), mit Wass	serstoff beha	ndelt, schwe	er			
	Acute fish toxicity	LC50 mg/l	>100		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>100		Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna		
111-76-2	2-butoxyethanol						
	Acute fish toxicity	LC50 mg/l	1474		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	1840		Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	1550	48 h	Daphnia magna		
	Fish toxicity	NOEC mg/l	>100		Brachydanio rerio (zebra-fish)		
	Crustacea toxicity	NOEC mg/l	>100	21 d	Daphnia magna		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of used product

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease,

soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother

liquors; hazardous waste

Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 10 of 12

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

Other applicable information (marine transport)

E0

14.6. Special precautions for user

Warning: Flammable gases. Persons employed in transporting dangerous goods must be trained. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 11 of 12

Other applicable information

Minimum amount regulations: < 1 litre

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

Information according to 2012/18/EU

P3a FLAMMABLE AEROSOLS

(SEVESO III):

Additional information

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,5,6,7,8,9,10,11,12,14,15.

These details refer to the products as it is delivered.

Notice the directions for use on the label.

* Data changed compared with the previous version

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Harmful if inhaled.

H332



according to Regulation (EC) No 1907/2006

VELIND Rostlöser mit MOS2 300ml

Revision date: 27.02.2019 Product code: 31019 Page 12 of 12

EUH066

Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)