according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013
Revision date 24th February 2025 Version 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier MA PROFESSIONAL UNDERSEAL

Substance / mixture mixture mixture Number M-24022025

UFI Y5DW-70V9-W00Y-NH35

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Impregnation (impregnating agent)

Main intended use

PP-BIO-7 Film preservatives

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name AMTRA Sp. z o. o.

Address Schonów 3, Sosnowiec, 41-200

Poland

 VAT Reg No
 PL6250009241

 Phone
 +48 32 294 41 00

 E-mail
 amtra@amtra.pl

Competent person responsible for the safety data sheet

Name AMTRA Sp. z o. o. E-mail amtra@amtra.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

P410+P412 P501

Protect from sunlight. Do no expose to temperatures exceeding 50 °C. Dispose of contents/container to according to applicable regulations.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	30-40	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	1, 2
CAS: 64742-48-9 EC: 919-857-5 Registration number: 01-2119463258-33- XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	15-20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	10-20	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	2
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	xylene	6-7	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 3
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6	ethanol	0.1-0.9	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	propan-2-ol	<0.05	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

3 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Not expected.

If in eyes

When intruding eyes, it can evoke irritation.

If swallowed

Not expected.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full iet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature is from +5 °C to +30 °C. Protect against frost. Protect from sunlight. Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Туре	Value
	OEL 8 hours	221 mg/m ³
vulene (CAC: 1220, 20, 7)	OEL 8 hours	50 ppm
xylene (CAS: 1330–20–7)	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

Notes

Skin.

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

It is not needed.

Skin protection

Hand protection:

Chemical resistant gloves should be worn whenever working with chemical products when a risk assessment indicates this is necessary.

The selected protective gloves must meet the requirements of the EN 374-1 standard. Recommended for long-term contact:

Material for protective gloves: nitrile rubber. Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Recommended for momentary contact: Material for protective gloves: nitrile rubber

Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state liquid Colour brown, black Odour characteristic Melting point/freezing point not determined Boiling point or initial boiling point and boiling range not determined Flammability inflammable Lower and upper explosion limit not determined Flash point not determined

Auto-ignition temperature not determined Decomposition temperature not determined рΗ non-soluble (in water)

Kinematic viscosity >20.5 mm²/s at 40 °C

Solubility in water insoluble Partition coefficient n-octanol/water (log value) not determined 3-6 bar Vapour pressure

propan-2-ol (CAS: 67-63-0) 43 hPa at 20 °C

Density and/or relative density

0.7-0.85 q/cm³ Density propan-2-ol (CAS: 67-63-0) 0.79 a/cm³ Relative vapour density not determined Particle characteristics not determined

9.2. Other information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

Page

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013
Revision date 24th February 2025 Version

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

6.0

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

MA PROFESS	MA PROFESSIONAL UNDERSEAL						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Dermal	ATE		15714 mg/kg				Calculation of value
Inhalation (dust/mist)	ATE		21.43 mg/l				Calculation of value

propan-2-ol							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Inhalation (vapor)	LC50	OECD 403	>10000 ppm	6 hours	Rat	F/M	

Skin corrosion/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Serious eye damage/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Route of exposure	Result	Method	Exposure time	Species		
Eye	Serious eye damage	OECD 405		Rabbit		

Respiratory or skin sensitisation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Route of exposure	Result	Exposure time	Species	Sex		
	Not sensitizing		Guinea-pig	F/M		

Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Result	Exposure time	Specific target organ	Species	Sex		
Negative without metabolic activation, Negative with metabolic activation		Ovary	Guinea-pig	F/M		

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2029

24th February 2025 Version 6.0

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Route of exposure	Parameter	Value	Result	Species	Sex	
Inhalation (vapor)	NOEC	500 ppm		Rat (Rattus norvegicus)	F/M	

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

propan-2-ol						
Parameter	Value	Exposure time	Species	Environment		
EC50	>10000 mg/l	48 hours	Daphnia (Daphnia magna)			
LC50	9640 mg/l	96 hours	Fish	Fresh water		

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code Safety signs 1950

2.1



Tunnel restriction code (D)

Air transport - ICAO/IATA

Packaging instructions passenger 203 Cargo packaging instructions 203

Marine transport - IMDG

EmS (emergency plan) F-D, S-U MFAG 620

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013
Revision date 24th February 2025 Version 6.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways. H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Guidelines for safe handling used in the safety data sheet

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to according to applicable regulations.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox. Acute toxicity

ADR European agreement concerning the international carriage of dangerous goods by

road

Aerosol Aerosol

Asp. Tox. Aspiration hazard
BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50 % of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013
Revision date 24th February 2025 Version 6.0

Eye Irrit. Eye irritation
Flam. Gas Flammable gas
Flam. Liq. Flammable liquid

IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

log KowOctanol-water partition coefficientNOECNo observed effect concentrationOELOccupational Exposure Limits

PBT Persistent, bioaccumulative and toxic

PMT Persistent, mobile and toxic

ppm Parts per million
Press. Gas Gases under pressure

Press. Gas (Comp.)

Gas under pressure: compressed gas

Press. Gas (Diss.)

Gas under pressure: dissolved gas

Press. Gas (Liq.)

Gas under pressure: liquefied gas

Press. Gas (Ref. Lig.) Gas under pressure: refrigerated liquefied gas

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 6.0 replaces the SDS version from Tuesday, 10 August 2021. Changes were made in sections 1, 2, 11, 12, 13, 15 and 16.

More information

Classification procedure - calculation method.

Statement

according to Commission Regulation (EU) 2020/878 as amended

MA PROFESSIONAL UNDERSEAL

Creation date 04th March 2013 Revision date 24th February 2025

Version 6.0

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.