



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_DE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Tectyl® CAVITY WAX AMBER
RUST PREVENTATIVE

Product code : 887097

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Corrosion inhibitor.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 0 30-1
92 40

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single
exposure, Category 3, Central nervous
system

H336: May cause drowsiness or dizziness.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, cyclenes, <2% aromatics	64742-48-9 919-857-5 01-2119463258-33-xxxx	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304	>= 20,00 - < 25,00
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22-xxxx	Eye Irrit.2; H319	>= 1,00 - < 2,50
2-(2-Heptadec-8-enyl- 2-imidazolin-1- yl)ethanol	95-38-5 202-414-9 01-2119777867-13-xxxx	Acute Tox.4; H302 Skin Corr.1C; H314 Eye Dam.1; H318 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,10 - < 0,25
(Z)-N-Methyl-N-(1-oxo- 9-octadecenyl)glycine	110-25-8 203-749-3 01-2119488991-20-xxxx	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute1; H400	>= 0,10 - < 0,25
Substances with a workplace exposure limit :			
Propane	74-98-6 200-827-9 01-2119486944-21-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 25,00 - < 40,00
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 15,00 - < 25,00
(2- Methoxymethylethoxy)p ropanol	34590-94-8 252-104-2 01-2119450011-60-xxxx		>= 1,00 - < 2,50

For explanation of abbreviations see section 16.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure. |
| In case of skin contact | : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist. |
| If swallowed | : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|--------------------------------------|
| Symptoms | : No symptoms known or expected. |
| Risks | : May cause drowsiness or dizziness. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--|
| Treatment | : No hazards which require special first aid measures. |
|-----------|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray |
|------------------------------|--|



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Unsuitable extinguishing media : Foam
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
sulfur compounds
Aldehydes

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	64742-48-9	AGW	300 mg/m ³	DE TRGS 900
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
(2-Methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
		AGW (Vapour and aerosols)	50 ppm 310 mg/m ³ Vapour and aerosols	DE TRGS 900

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol	: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 0,46 mg/m³RD TOX - Repeated dose toxicity End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 14 mg/m³RD TOX - Repeated dose toxicity End Use: Workers Exposure routes: Dermal
--	---



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Potential health effects: Long-term systemic effects
Value: 0,06 mg/kgRD TOX - Repeated dose toxicity
End Use: Workers
Exposure routes: Dermal
Potential health effects: Acute systemic effects
Value: 2 mg/kgRD TOX - Repeated dose toxicity

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol	: Sewage treatment plant
	Value: 0,27 mg/l
	Fresh water sediment
	Value: 0,376 mg/kg
	Marine sediment
	Value: 0,0376 mg/kg
	Soil
	Value: 0,075 mg/kg
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	: Sewage treatment plant
	Value: 13 mg/l

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Material : nitrile rubber
Break through time : 480 min
Glove thickness : 0,38 mm

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Respiratory protection	: In the case of vapour formation use a respirator with an approved filter. In the case of dust or aerosol formation use respirator with an approved filter.
Filter type	: Combined particulates, organic gas and low boiling vapour type (AX-P) In the case of vapour formation use a respirator with an approved filter. In the case of dust or aerosol formation use respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: aerosol
Colour	: amber
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: < 0 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0,70 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Vapours may form explosive mixture with air.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks. excessive heat Do not allow evaporation to dryness. Exposure to air.
---------------------	---	--



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

10.5 Incompatible materials

Materials to avoid : Acids
Oxidizing agents
salts of strong bases
strong bases

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Acute oral toxicity	: LD50 (Rat, male and female): > 15.000 mg/kg Method: OECD Test Guideline 423 Remarks: Information given is based on data obtained from similar substances.
Acute inhalation toxicity	: LC50 (Rat): > 4,95 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests. Remarks: Information given is based on data obtained from similar substances.
Acute dermal toxicity	: LD50 (Rabbit, male and female): >= 3.160 mg/kg Method: OECD Test Guideline 402 Assessment: No adverse effect has been observed in acute dermal toxicity tests. Remarks: Information given is based on data obtained from similar substances.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Components:

SODIUM PETROLEUM SULFONATE:

Acute oral toxicity	: LD50 (Rat): > 5 g/kg LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401 GLP: yes Remarks: Information given is based on data obtained from similar substances.
Acute inhalation toxicity	: LC50 (Rat): > 1,9 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: yes Assessment: The component/mixture is classified as acute inhalation toxicity, category 5. Remarks: No mortality observed at this dose. Information given is based on data obtained from similar substances.
Acute dermal toxicity	: LD50 (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402 GLP: yes Remarks: No mortality observed at this dose. Information given is based on data obtained from similar substances.

Components:

OLEYL HYDROXYETHYL IMIDAZOLINE:

Acute oral toxicity	: LD50 (Rat): ca. 1.265 mg/kg
---------------------	-------------------------------

Components:

OLEYL N-METHYLGLYCINE:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 1,01 - 1,85 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Components:

PROPANE:

Acute inhalation toxicity	: LC50 (Rat): 1.237 mg/l Exposure time: 2 h Test atmosphere: gas
---------------------------	--



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Assessment: **Not classified as acutely toxic by inhalation under GHS.**
Remarks: **Information given is based on data obtained from similar substances.**

Components:

BUTANE NORMAL:

Acute inhalation toxicity : **LC50 (Mouse): 680 mg/l**
Exposure time: **2 h**

LC50 (Rat): > 50000 ppm
Exposure time: **2 h**
Test atmosphere: **gas**

Components:

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Acute oral toxicity : **LD50 (Rat): > 5.000 mg/kg**
Method: **OECD Test Guideline 401**

Acute inhalation toxicity : **LC0 (Rat, female): > 553 ppm**
Exposure time: **8 h**
Test atmosphere: **vapour**
Method: **OECD Test Guideline 403**
Remarks: **No mortality observed at this dose.**

Acute dermal toxicity : **LD50 (Rat): > 5.000 mg/kg**

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Result: **Slight, transient irritation**

SODIUM PETROLEUM SULFONATE:

Species: **Rabbit**
Result: **Slight, transient irritation**
Remarks: **Information given is based on data obtained from similar substances.**

OLEYL HYDROXYETHYL IMIDAZOLINE:

Species: **Rabbit**
Method: **OECD Test Guideline 404**
Result: **Corrosive after 1 to 4 hours of exposure**

OLEYL N-METHYLGLYCINE:

Species: **Rabbit**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Result: **Irritating to skin.**

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Species: **Rabbit**

Result: **No skin irritation**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Result: **No eye irritation**

SODIUM PETROLEUM SULFONATE:

Species: **Rabbit**

Result: **Irritating to eyes.**

Remarks: **Information given is based on data obtained from similar substances.**

OLEYL HYDROXYETHYL IMIDAZOLINE:

Result: **Corrosive**

OLEYL N-METHYLGLYCINE:

Species: **Rabbit**

Result: **Corrosive**

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Species: **Rabbit**

Result: **Slight, transient irritation**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

SODIUM PETROLEUM SULFONATE:

Assessment: **Does not cause skin sensitisation.**

Remarks: **Information given is based on data obtained from similar substances.**

OLEYL HYDROXYETHYL IMIDAZOLINE:

Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

Method: **OECD Test Guideline 406**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

OLEYL N-METHYLGLYCINE:

Test Type: **Maximisation Test**
Species: **Guinea pig**
Assessment: **Does not cause skin sensitisation.**

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Species: **Humans**
Assessment: **Does not cause skin sensitisation.**

Germ cell mutagenicity

Not classified based on available information.

Components:

SODIUM PETROLEUM SULFONATE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

OLEYL N-METHYLGLYCINE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

PROPANE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

OLEYL HYDROXYETHYL IMIDAZOLINE:

Exposure routes: Ingestion

Target Organs: Gastrointestinal tract, thymus gland

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

DIPROPYLENE GLYCOL MONOMETHYL ETHER:

Remarks: Central nervous system



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout))**: > 1.000 mg/l
Exposure time: 96 h
Test Type: **semi-static test**
Test substance: **WAF**
Method: **OECD Test Guideline 203**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea))**: 1.000 mg/l
Exposure time: 48 h
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 202**

Toxicity to algae : **EL50 (Pseudokirchneriella subcapitata (green algae))**: > 1.000 mg/l
End point: **Growth inhibition**
Exposure time: 72 h
Test Type: **static test**
Method: **OECD Test Guideline 201**

Sulfonic acids, petroleum, sodium salts

Toxicity to fish : **LL50 (Pimephales promelas (fathead minnow))**: > 1.000 mg/l
Exposure time: 96 h
Test Type: **Renewal**
Test substance: **WAF**
Method: **OECD Test Guideline 203**
GLP: **yes**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea))**: > 1.000 mg/l
Exposure time: 48 h
Test Type: **static test**
Test substance: **WAF**
Remarks: **Information given is based on data obtained from similar substances.**

Toxicity to algae : **NOEC (Pseudokirchneriella subcapitata (green algae))**: > 1.000 mg/l
End point: **Growth inhibition**
Exposure time: 72 h
Test Type: **static test**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Test substance: **WAF**

Remarks: **Information given is based on data obtained from similar substances.**

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Toxicity to fish : **LC50 (Danio rerio (zebra fish)): 0,3 mg/l**
Exposure time: **96 h**
Test Type: **static test**
Method: **OECD Test Guideline 203**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): 0,163 mg/l**
Exposure time: **48 h**
Test Type: **semi-static test**
Method: **OECD Test Guideline 202**

Toxicity to algae : **EC50 (Desmodesmus subspicatus (green algae)): 0,03 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**
Method: **OECD Test Guideline 201**

M-Factor (Short-term (acute) aquatic hazard) : **10**

M-Factor (Long-term (chronic) aquatic hazard) : **1**

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

Toxicity to fish : **LC50 (Leuciscus idus (Golden orfe)): 9,3 mg/l**
Exposure time: **96 h**
Test Type: **static test**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): 0,43 mg/l**
Exposure time: **48 h**
Test Type: **static test**

Toxicity to algae : **EC50 (Desmodesmus subspicatus (green algae)): 6,3 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**

Butane

Toxicity to fish : Remarks: **No toxicity at the limit of solubility QSAR**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l**
Exposure time: **48 h**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

	Remarks: QSAR
Toxicity to algae	: EC50 (green algae): Expected 7,7 mg/l Exposure time: 96 h Remarks: QSAR
(2-Methoxymethylethoxy)propanol	
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 10.000 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia magna (Water flea)): 1.919 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 969 mg/l End point: Growth inhibition Exposure time: 72 h

12.2 Persistence and degradability

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics

Biodegradability : Result: **Readily biodegradable.**
Biodegradation: **80 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301F**

Sulfonic acids, petroleum, sodium salts

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **8 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301D**
Remarks: **Information given is based on data obtained from similar substances.**

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **1 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

Biodegradability : Result: **Readily biodegradable.**
Biodegradation: **85 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Butane

Biodegradability : Result: **Readily biodegradable.**
Remarks: **Information given is based on data obtained from similar substances.**

(2-Methoxymethylethoxy)propanol

Biodegradability : Result: **Readily biodegradable.**
Biodegradation: **75 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301F**

Chemical Oxygen Demand (COD) : **2,02 mg/g**

ThOD : **2,06 mg/g**

12.3 Bioaccumulative potential

Components:

Sulfonic acids, petroleum, sodium salts

Partition coefficient: n-octanol/water : log Pow: **Calculated > 10**

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol

Partition coefficient: n-octanol/water : log Pow: **8**

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine

Partition coefficient: n-octanol/water : log Pow: **3,5 - 4,2**

Propane

Partition coefficient: n-octanol/water : log Pow: **2,36**

Butane

Partition coefficient: n-octanol/water : log Pow: **2,89**

(2-Methoxymethylethoxy)propanol

Partition coefficient: n-octanol/water : log Pow: **0,004**

12.4 Mobility in soil

No data available



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)
Packing instruction (passenger aircraft) : 203



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

		Quantity 1	Quantity 2
8	Extremely flammable	10 t	50 t
9b	Dangerous for the environment	200 t	500 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Water contaminating class (Germany) : WGK 2 obviously hazardous to water
Remarks: VWWWS A4

TA Luft List (Germany) : Total dust:
Not applicable
Inorganic substances in powdered form:
Not applicable
Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
portion Class 1: 1,98 %

Carcinogenic substances:
portion Class 3: < 0,01 %

Mutagenic:
others: < 0,01 %

Toxic to reproduction:
Not applicable

Other regulations:



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: Not in compliance with the inventory
TSCA	: On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : R0524073

Full text of H-Statements

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization



SAFETY DATA SHEET

Tectyl® CAVITY WAX AMBER RUST
PREVENTATIVE

Version: 5.0

Revision Date: 14.04.2020

Print Date: 13/05/2020

logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-pharse : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-pharse: Safety phrase
WGK : German Water Hazard Class