



SAFETY DATA SHEET

600 Silver Paint

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	600 Silver Paint
Product number	RF0145C
UFI	UFI: 9CR8-Y148-500F-DJQ1
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product. Paint.
-----------------	---------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	Holt Lloyd Services 52 Rue des 40 Mines, 60000 – Allonne, France Phone: +33 (0)3 64 99 00 32 info@holtsauto.com
Contact person	Contact email address: info@holtsauto.com
Manufacturer	Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs
---------------------	--

600 Silver Paint

National emergency telephone number +43 1 31304 5620; chemikalien@umweltbundesamt.at (Austria)
 +32022649636; info@poisoncentre.be (Belgium)
 +359 2 9154 409; poison_centre@mail.orbitel.bg (Bulgaria)
 +38514686910; toksikologija@hzjz.hr (Croatia)
 +35722405611; cy-chemregistry@dli.mlsi.gov.cy (Cyprus)
 +420267082257; biocidy@mzcr.cz (Czech Republic)
 +45 72 54 40 00; mst@mst.dk (Denmark)
 +372 794 3500; clp@terviseamet.ee, info@terviseamet.ee (Estonia)
 +358 5052 000; kirjaamo@tukes.fi (Finland)
 + 33 3 83 85 21 92; bnpc@chru-nancy.fr (France)
 +49-30-18412-0; bfr@bfr.bund.de (Germany)
 +302106479250; +302106479450; devxp.gcsf@aade.gr, environment.gcsf@aade.gr (Greece)
 +36 (1) 476 1135; clp.ca@nnk.gov.hu (Hungary)
 +354 543 22 22; eitur@landspitali.is (Iceland)
 +353 (1) 809 2166 / +353 (1) 809 2566; chemicalsinfo@beaumont.ie (Ireland)
 +390649906140; inscweb@iss.it (Italy)
 +371 67032600; lvgmc@lvgmc.lv (Latvia)
 +370 70662008; aaa@aaa.am.lt (Lithuania)
 +320 22649636; +352 24785551; info@poisoncentre.be; direction-sante@ms.etat.lu (Luxembourg)
 +356 2395 2000; info@mccaa.org.mt (Malta)
 +31 88 75 585 61; productnotificatie@umcutrecht.nl (The Netherlands)
 +4573580500; produktregisteret@miljodir.no / +47 21 07 70 00; folkehelseinstituttet@fhi.no (Norway)
 +48 42 2538 400; biuro@chemikalia.gov.pl (Poland)
 +351 800 250 250; ciav.tox@inem.pt (Portugal)
 +40213183606; infotox@insp.gov.ro (Romania)
 +7 495 621 6885; +7 495 628 1687; rtiac@mail.ru; rtiac2003@yahoo.com (Russia)
 +421 2 5465 2307; ntic@ntic.sk (Slovakia)
 + 386 1 522 1293; gp.ukc@kclj.si (Slovenia)
 +34 917689800; intcf.doc@justicia.es (Spain)
 +46104566750; giftinformation@gic.se (Sweden)
 +44 121 507 4123; allistervale@npis.org, sallybradberry@npis.org (UK)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

600 Silver Paint

Hazard statements	<p>H222 Extremely flammable aerosol.</p> <p>H229 Pressurised container: may burst if heated.</p> <p>H315 Causes skin irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
UFI	UFI: 9CR8-Y148-500F-DJQ1
Contains	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Hydrocarbons, C9, Aromatics, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Supplementary precautionary statements	<p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			10-30%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35-XXXX	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
PROPANE			10-30%
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21-XXXX	
Classification Flam. Gas 1A - H220			

600 Silver Paint

ISOBUTANE 10-30%		
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: 01-2119485395-27-XXXX
Classification Flam. Gas 1A - H220 Press. Gas		
BUTANE 10-30%		
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-XXXX
Classification Flam. Gas 1A - H220 Press. Gas		
XYLENE 10-30%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		
Hydrocarbons, C9, Aromatics 1-5%		
CAS number: 128601-23-0	EC number: 918-668-5	REACH registration number: 01-2119455851-35-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 1-5%		
CAS number: 64742-48-9	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304		

600 Silver Paint

ETHYLBENZENE		1-5%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-XXXX
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.
Skin contact	Wash skin thoroughly with soap and water or use an approved skin cleanser. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause drowsiness or dizziness.
Ingestion	The product is not believed to present a hazard due to its physical nature.
Skin contact	Causes skin irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments	Treat symptomatically.
----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Move containers from fire area if it can be done without risk.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment.
----------------------------------	-----------------------------------

600 Silver Paint

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

XYLENE (CAS: 1330-20-7)

DNEL

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day

Workers - Dermal; Long term systemic effects: 180 mg/kg/day

Consumer - Inhalation; Short term local effects: 174 mg/m³

Consumer - Inhalation; Short term systemic effects: 174 mg/m³

Workers - Inhalation; Short term systemic effects: 289 mg/m³

Workers - Inhalation; Short term local effects: 289 mg/m³

Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³

Workers - Inhalation; Long term systemic effects: 77 mg/m³

Hydrocarbons, C9, Aromatics (CAS: 128601-23-0)

600 Silver Paint

DNEL

Workers - Inhalation; Long term systemic effects: 150 mg/m³
 Workers - Dermal; Long term systemic effects: 25 mg/kg bw/day
 General population - Inhalation; Long term systemic effects: 32 mg/m³
 General population - Dermal; Long term systemic effects: 56 mg/kg bw/day
 General population - Oral; Long term systemic effects: 56 mg/kg bw/day

ETHYLBENZENE (CAS: 100-41-4)

DNEL

Workers - Inhalation; Long term systemic effects: 77 mg/m³
 Workers - irritation (respiratory tract); Short term Acute: 293 mg/m³
 Workers - Dermal; Long term systemic effects: 180 mg/kg/day
 Workers - Hazard for the eyes
 low hazard (no threshold derived)
 General population - Inhalation; Long term systemic effects: 15 mg/m³
 General population - Oral; Long term systemic effects: 1.6 mg/kg/day
 General Population - Hazard for the eyes
 low hazard (no threshold derived)

PNEC

Fresh water; 0.1 mg/l
 Intermittent release, Fresh water; 0.1 mg/l
 marine water; 0.01 mg/l
 STP; 9.6 mg/l
 Sediment (Freshwater); 13.7 mg/kg sediment dry weight
 Sediment (Marinewater); 1.37 mg/kg sediment dry weight
 Soil; 2.68 mg/kg soil dry weight
 Secondary Poisoning (Hazard for Predators) - Oral; 200 mg/kg food

8.2. Exposure controls

Protective equipment



Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Silver.
Odour	Characteristic.
Flash point	< 0°C

600 Silver Paint

Upper/lower flammability or explosive limits Lower flammable/explosive limit: 1.5% Upper flammable/explosive limit: 9.0%

Relative density ~ 0.695 @ 20°C

9.2. Other information

Volatility 95.6%

Volatile organic compound This product contains a maximum VOC content of 695 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Information given is based on data of the components and of similar products.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 16,000.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (gases ppm) 180,722.89

ATE inhalation (vapours mg/l) 73.38

ATE inhalation (dusts/mists mg/l) 60.24

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

600 Silver Paint

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. Symptoms following overexposure may include the following: Headache.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Causes skin irritation.

Eye contact May cause temporary eye irritation.

Route of exposure Inhalation Skin and/or eye contact

Toxicological information on ingredients.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) LD₅₀ > 5840 mg/kg, Oral, Rat

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

600 Silver Paint

Acute toxicity dermal (LD₅₀ 2,920.0 mg/kg)

Species Rabbit

Notes (dermal LD₅₀) LD₅₀ > 2920 mg/kg, Dermal, Rabbit

ATE dermal (mg/kg) 2,920.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 25.2

Species Rat

ATE inhalation (vapours mg/l) 25.2

PROPANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

ISOBUTANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

BUTANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,523.0

Species Rat

ATE oral (mg/kg) 3,523.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

600 Silver Paint

Species	Rabbit
ATE dermal (mg/kg)	2,000.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	29,000.0
Species	Rat
Species	Human
ATE inhalation (vapours mg/l)	11.0
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Causes skin irritation.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes serious eye irritation.
<u>Carcinogenicity</u>	
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways.

ETHYLBENZENE

<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	LD ₅₀ 3500 mg/kg, Oral, Rat
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	LD ₅₀ 15400 mg/kg, Dermal, Rabbit
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Harmful if inhaled. LC50 17629 mg/m ³ , Inhalation, Mouse
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No information available.
<u>Skin sensitisation</u>	
Skin sensitisation	No adverse effects observed (not sensitising)
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No adverse effects observed (negative)
Genotoxicity - in vivo	No adverse effects observed (negative)
<u>Carcinogenicity</u>	

600 Silver Paint

Carcinogenicity	NOAEC 1085.13 mg/m ³ , Inhalation, Rat Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEC 4342.13 mg/m ³ , Inhalation, Rat F1 Based on available data the classification criteria are not met.
Reproductive toxicity - development	Developmental toxicity: - NOAEL: 750 mg/kg/day, Oral, Rat Developmental toxicity: - NOAEC: 434.21 mg/m ³ , Inhalation, Mouse No evidence of reproductive toxicity in animal studies.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Conclusive data but not sufficient for classification.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Target organs	Hearing organs
<u>Aspiration hazard</u>	
Aspiration hazard	May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Ecological information on ingredients.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 11.4 hours: 96 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 3 hours: 48 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 30-100 hours: 72 mg/l, Algae

XYLENE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 13.5 hours: 96 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 7.4 hours: 48 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 1-10 mg/l, Algae

ETHYLBENZENE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 4.2 mg/l, Oncorhynchus mykiss (Rainbow trout) LC ₅₀ , 96 hours: 5.1 mg/l, Menidia menidia (Atlantic silverside)
------------------------------	--

600 Silver Paint

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1.8 mg/l, Daphnia magna LC ₅₀ , 48 hours: 3.2 mg/l, Ceriodaphnia dubia LC ₅₀ , 96 hours: 2.6 mg/l, Mysid shrimp, Americamysis bahia
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 3.6 mg/l, Pseudokirchneriella subcapitata EC ₁₀ , NOEC, 96 hours: 3.4 mg/l, Pseudokirchneriella subcapitata EC ₅₀ , 96 hours: 7.7 mg/l, Skeletonema costatum EC ₁₀ , NOEC, 96 hours: 4.5 mg/l, Skeletonema costatum
Acute toxicity - microorganisms	EC ₅₀ , 24 hours: 96 mg/l, Nitrosomonas sp.
Acute toxicity - terrestrial	LC ₅₀ , 48 hours: 0.047 mg/cm ² , Eisenia Fetida (Earthworm)
Chronic aquatic toxicity	
Chronic toxicity - aquatic invertebrates	LC ₅₀ , 7 days: 3.6 mg/l, Ceriodaphnia dubia NOEL, 7 days: 1.0 mg/l, Ceriodaphnia dubia

12.2. Persistence and degradability

Ecological information on ingredients.

XYLENE

Biodegradation	The substance is readily biodegradable.
-----------------------	---

ETHYLBENZENE

Persistence and degradability	Rapidly degradable 28 days 79%
Phototransformation	Air - Half-life 50%: 2.3 days

12.3. Bioaccumulative potential

Ecological information on ingredients.

ETHYLBENZENE

Bioaccumulative potential	BCF: 110, QSAR
Partition coefficient	Log Kow (Log Pow): 3.6 @ 20 deg C

12.4. Mobility in soil

Mobility	The product contains organic solvents which will evaporate easily from all surfaces.
-----------------	--

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

ETHYLBENZENE

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

600 Silver Paint

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion.

Waste class WGK : 2 (Germany)

SECTION 14: Transport information

General As supplied, this product is consigned under the Limited Quantities provisions.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS (CONTAINS Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Hydrocarbons, C9, Aromatics)

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

14.5. Environmental hazards

600 Silver Paint

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.
Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

600 Silver Paint

Abbreviations and acronyms used in the safety data sheet

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ATE: Acute Toxicity Estimate.
 BCF: Bioconcentration Factor.
 BOD: Biochemical Oxygen Demand.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 EC₅₀: 50% of maximal Effective Concentration.
 GHS: Globally Harmonized System.
 IARC: International Agency for Research on Cancer.
 IATA: International Air Transport Association.
 IBC: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code).
 ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IMDG: International Maritime Dangerous Goods.
 Kow: Octanol-water partition coefficient.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 LOAEC: Lowest Observed Adverse Effect Concentration.
 LOAEL: Lowest Observed Adverse Effect Level.
 LOEC: Lowest Observed Effect Concentration.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 NOAEC: No Observed Adverse Effect Concentration.
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 SVHC: Substances of Very High Concern.
 UVCB - Unknown or variable composition, complex reaction products or Biological materials.
 vPvB: Very Persistent and Very Bioaccumulative.

Classification procedures according to Regulation (EC) 1272/2008

Aerosol 1 - H222, H229: Calculation method. Skin Irrit. 2 - H315: Calculation method. STOT SE 3 - H336: Calculation method. Aquatic Chronic 2 - H411: Calculation method.

Issued by	Regulatory Specialist
Revision date	14/12/2021
Revision	11
Supersedes date	01/08/2018
SDS number	14354

600 Silver Paint

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.