

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Hypercoat -High Gloss Protection- EVOLUTION

Article number:

06776000, 06777050, 06779000

UFI: 9TU0-3047-500M-7WDD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains Tetramethyl Acetyloctahydronaphtalenes. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

GB

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Care components in aqueous solution

Dangerous components:

CAS: 71750-79-3 EC number: 615-336-9	Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me ⚠ Skin Corr. 1B, H314	15-<20%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-<15%
CAS: 5131-66-8 EINECS: 225-878-4 Reg.nr.: 01-2119475527-28-xxxx	3-butoxypropan-2-ol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-<10%
CAS: 69011-36-5 EC No 931-138-8	isotridecanol,ethoxylated (>5-20EO) ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 1 % ≤ C < 10 %	3-<5%
CAS: 64-19-7 EINECS: 200-580-7 Reg.nr.: 01-2119475328-30	acetic acid 99/100 % ⚠ Flam. Liq. 3, H226; ⚠ Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 % Skin Corr. 1B; H314: 25 % ≤ C < 90 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Dam. 1; H318: C ≥ 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	1-<3%
EC No 915-730-3 Reg.nr.: 01-2119489989-04-xxxx	Tetramethyl Acetyloctahydronaphtalenes Contains: 54464-57-2 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone; 68155-66-8 1-(1,2,3,5,6,7,8,8a-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one; 68155-67-9 1-(1,2,3,4,6,7,8,8a-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317	<0.25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact:

Rinse opened eye for several minutes under running water.

Seek immediate medical advice.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation / Eye damage

Caustic effect on skin and mucous membranes.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed*Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Water haze**Carbon dioxide**Fire-extinguishing powder**Foam***For safety reasons unsuitable extinguishing agents:** *Water with full jet***5.2 Special hazards arising from the substance or mixture***In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO₂)**Silicon oxides**Nitrogen oxides (NO_x)***5.3 Advice for firefighters****Protective equipment:***Wear fully protective suit.**Do not enter the hazardous area without a self-contained breathing apparatus.**See Section 8 for information on personal protection equipment.***Additional information***Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Ensure adequate ventilation***6.2 Environmental precautions:***Do not allow to penetrate the ground/soil.**Do not allow to enter sewers/ surface or ground water.***6.3 Methods and material for containment and cleaning up:***Ensure adequate ventilation.**Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to item 13.***6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****7.1 Precautions for safe handling***Ensure good ventilation/exhaustion at the workplace.**Open and handle receptacle with care.***Information about fire - and explosion protection:** *Keep ignition sources away - Do not smoke.***7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** *Prevent any seepage into the ground.***Information about storage in one common storage facility:***Store away from foodstuffs.**Store away from oxidising agents.***Further information about storage conditions:***Keep container tightly sealed.**Store receptacle in a well ventilated area.**Protect from heat and direct sunlight.**Protect from frost.**Recommended storage temperature: 20 °C.*

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:
CAS: 107-98-2 1-Methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin

CAS: 64-19-7 acetic acid 99/100 %

WEL (Great Britain)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm
IOELV (EU)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm

Regulatory information

WEL (Great Britain): EH40/2018

IOELV (EU): (EU) 2017/164

DNELs

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	DNEL	3.3 mg/kg (consumer) (long-term / systemic effects)
Dermal	DNEL	18.1 mg/kg (consumer) (long-term / systemic effects) 50.6 mg/kg (worker) (long-term / systemic effects)
Inhalative	DNEL	43.9 mg/m ³ (consumer) (long-term / systemic effects) 553.5 mg/m ³ (worker) (short-term / local effects) 369 mg/m ³ (worker) (long-term / systemic effects)

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	DNEL	12.5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	22 mg/kg (consumer) (longterm systematic effects) 52 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	43 mg/m ³ (consumer) (longterm systematic effects) 147 mg/m ³ (worker) (longterm systematic effects)

CAS: 64-19-7 acetic acid 99/100 %

Inhalative	DNEL	25 mg/m ³ (consumer) (acute local effect) 25 mg/m ³ (consumer) (longterm local effect) 25 mg/m ³ (worker) (longterm local effect)
------------	------	--

PNECs

CAS: 107-98-2 1-Methoxy-2-propanol

PNEC	100 mg/l (STP) 100 mg/l (water (intermittent release)) 10 mg/l (water (fresh water)) 1 mg/l (water (sea water))
PNEC	2.47 mg/kg (gro) 41.6 mg/kg (sediment (fresh water)) 4.17 mg/kg (sediment (sea water))

CAS: 5131-66-8 3-butoxypropan-2-ol

PNEC	10 mg/l (sewage plant) 5.25 mg/l (sporadic release) 0.525 mg/l (water (fresh water)) 0.0525 mg/l (water (sea water))
------	---

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 4)

PNEC	2.36 mg/kg (sediment (fresh water)) 0.236 mg/kg (sediment (sea water)) 0.16 mg/kg (soil)
CAS: 64-19-7 acetic acid 99/100 %	
PNEC	30.58 mg/l (sporadic release) 85 mg/l (STP) 3.058 mg/l (freshwater (Süßwasser)) 0.3058 mg/l (water (sea water))
PNEC	11.36 mg/kg (sediment (fresh water)) 0.478 mg/kg (soil) 1.136 mg/kg (water (sea water))

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Ensure good ventilation/exhaustion at the workplace.

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Filter A/P2

[DIN EN 14387]

Protection of hands: Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 5 (> 240 min)

Eye protection:



Tightly sealed goggles

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Amber coloured
Odour:	Fruit-like
Odour threshold:	Not determined.

pH-value at 20 °C: 5.0 - 6.0

Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 100 - 175 °C

Flash point: 69 °C (DIN 51755)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 5)

Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.99 - 1.00 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Flow time at 20 °C	12 - 17 s (DIN EN ISO 2431/4mm)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Protect from heat.

See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

10.6 Hazardous decomposition products:

Carbon monoxide

Carbon dioxide (CO₂)

Nitrogen oxides (NO_x)

Silicon oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 71750-79-3 Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

Inhalative	LC0 / 6h	>7,000 ppm (rat)
------------	----------	------------------

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	LD50	3,300 mg/kg (rat) (OECD 401)
------	------	------------------------------

Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
--------	------	-------------------------------

Inhalative	LC50 / 4h	>3.5 mg/l (rat) (OECD 403)
------------	-----------	----------------------------

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 6)

CAS: 69011-36-5 isotridecanol,ethoxylated (>5-20EO)

Oral	ATE	500 mg/kg (Ratte)
------	-----	-------------------

CAS: 64-19-7 acetic acid 99/100 %

Oral	LD50	3,310 mg/kg (rat)
Dermal	DNEL	25 mg/m ³ (worker) (ackute local effect)
Inhalative	LC50/4d	40 mg/l (rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity** There are no ecotoxicological data available on this mixture.**Aquatic toxicity:****CAS: 107-98-2 1-Methoxy-2-propanol**

LC50 / 96h	>6,800 mg/l (Leuciscus idus) (DIN38412)
LC50 / 48h	23,300 mg/l (Daphnia magna)
EC50	>1,000 mg/l (Pseudokirchneriella subcapitata) (7d)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)

CAS: 5131-66-8 3-butoxypropan-2-ol

LC50 / 96h	>560-1,000 mg/l (Poecilla reticulata) (OECD 203)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)
EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD 202)
EC50 / 96 h	>1,000 mg/l (Pseudokirchneriella subcapitata)

CAS: 64-19-7 acetic acid 99/100 %

LC50 / 96h	75 mg/l (Lepomis macrochirus)
	>300.82 mg/l (Oncorhynchus mykiss) (OECD 203)
EC10 / 5h	1,000 mg/l (Pseudomonas putida)
EC50 / 48h	>300.82 mg/l (Daphnia magna)
EC50 / 72h	>300.82 mg/l (algae)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 107-98-2 1-Methoxy-2-propanol

Biodegradation	90-100 % (OECD 301E)
----------------	----------------------

CAS: 5131-66-8 3-butoxypropan-2-ol

Biodegradation	90 % (OECD301E/92/69/EWG, C4.-B)
----------------	----------------------------------

CAS: 64-19-7 acetic acid 99/100 %

Biodegradation	95 %
----------------	------

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 7)

12.3 Bioaccumulative potential**CAS: 107-98-2 1-Methoxy-2-propanol**

log Kow ≤0.43 log Kow (25°C)

CAS: 64-19-7 acetic acid 99/100 %

log Kow ≤0.17 log Kow

12.4 Mobility in soil No further relevant information available.**Additional ecological information:****General notes:**

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

07 06 04* other organic solvents, washing liquids and mother liquors

Uncleaned packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

Recommendation:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

Recommended cleansing agents: Water

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1760

14.2 UN proper shipping name

ADR

1760 CORROSIVE LIQUID, N.O.S. (AMINO FUNCTIONAL SILOXANE, ACETIC ACID, GLACIAL)

IMDG, IATA

CORROSIVE LIQUID, N.O.S. (AMINO FUNCTIONAL SILOXANE, ACETIC ACID, GLACIAL)

14.3 Transport hazard class(es)

ADR, IMDG, IATA

**Class**
Label8 Corrosive substances.
8**14.4 Packing group**

ADR, IMDG, IATA

II

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user

Warning: Corrosive substances.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 8)

Transport/Additional information:

ADR

Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	E

UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (AMINO FUNCTIONAL SILOXANE, ACETIC ACID, GLACIAL), 8, II
------------------------	---

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---------------------------	--

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

DGR: Przepisy dotyczące towarów niebezpiecznych - Dangerous Goods Regulations by IATA

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 3.00

Revision: 20.05.2020

(Contd. of page 9)

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Version history and indication of changes: Replaces version 2.00.*** Data compared to the previous version altered.**

GB