Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

· Article number: 002235

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the preparation: in accordance with product designation
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

EUROLUB GmbH

Freisinger Strasse 25-27 85386 Eching bei München Telefon: 08165/95 91 - 0 Fax: 08165/95 91 - 20

Email: info@eurolub.de

· Further information obtainable from:

Telefon: +49-(0)8165 / 95 91-0 (über Zentrale vermittelt)

Email: info@eurolub.de

· Emergency telephone number:

Beratungsstelle bei Vergiftungen, Mainz

Tel. 0049 (0) 6131 / 19240

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02
- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
+P412	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Additional information:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1, H220; Press. Gas, H280	50-100%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1	Naphtha (petroleum), hydrotreated light	15-<20%
	♠ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	
CAS: 64742-81-0 EINECS: 265-184-9	Kerosine (petroleum), hydrodesulfurized	10-<20%
Index number: 649-423-00-8	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 74-98-6 EINECS: 200-827-9	propane	10-<25%
	♦ Flam. Gas 1, H220; Press. Gas, H280	
Regulation (EC) No 648/2004	4 on detergents / Labelling for contents	
aliphatic hydrocarbons		≥ 30%

4 First aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up: Ensure adequate ventilation.

(Contd. on page 4)

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Recommended storage temperature: 10-30 °C.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	DNEL	699 mg/kg/bw/day (population)
Dermal	DNEL	699 mg/kg bw/day (population)
		773 mg/kg bw/day (worker)
Inhalative	DNEL	608 mg/m³ (population)
		$2035 \text{ mg/m}^3 \text{ (worker)}$

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

(Contd. on page 5)

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 4)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · As protection from splashes gloves made of the following materials are suitable: PVC or PE gloves
- · Eye protection:



Tightly sealed goggles

· Body protection: Light weight protective clothing

9 Physical and chemical properties

9 Physicai ana chemicai pro	perues
Information on basic physical General Information	and chemical properties
· Appearance:	
Form:	Aerosol
Colour:	Brown
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not applicable for an aerosol *
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	310 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Protect from sunlight and temperatures above 50 °C. Development of explosive vapor/air mixtures.
· Explosion limits:	
Lower:	0,9 Vol %
Upper:	10,9 Vol %
· Vapour pressure at 20 °C:	4200 hPa
· Density at 20 °C:	$0,655 \text{ g/cm}^3$

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

	(Contd. of page 5
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	99,40 %
VOCV (CH)	99,30 %
· Other information	* The final mixture in the aerosol is formed only after the addition of the pressurized gas. Some data are not measurable in a hermetically sealed, pressurized container.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

Acute toxi	cuy.		
· LD/LC50	· LD/LC50 values relevant for classification:		
106-97-8	106-97-8 butane		
Inhalative	LC50/4 h	658 mg/l (rat)	
64742-49-	64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rab)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
74-98-6 pt	74-98-6 propane		
Inhalative	LC50/4 h	>20 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 6)

12 Ecological information

· Toxicity

· Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 1-10 mg/l (aquatische Invertebraten)

LC50 1-10 mg/l (fish)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

 $Do \ not \ allow \ undiluted \ product \ or \ large \ quantities \ of \ it \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
16 05 04*	gases in pressure containers (including halons) containing dangerous substances	
15 01 04	metallic packaging	
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

7 4 1			
IA	Transport	Intori	nation

· UN-Number · ADR, IMDG, IATA	UN1950
UN proper shipping nameADRIMDGIATA	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS AEROSOLS, flammable

(Contd. on page 8)

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 7)

· Transport hazard class(es)

 $\cdot ADR$



· Class
· Label
2 5F Gases.
2.1

· IMDG, IATA



· Class
· Label
2.1
2.1

· Packing group

· ADR, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Gases.

· Danger code (Kemler):

 \cdot EMS Number: F-D,S-U

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

. ADR

Limited quantities (LQ)
Transport category
Tunnel restriction code

· UN ''Model Regulation'': UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Printing date 17.06.2019 Version number 10 Revision: 17.06.2019

Trade name: Eurolub MoS2 Schmier- & Kriechöl - 400 ml

(Contd. of page 8) H411 Toxic to aquatic life with long lasting effects.

- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness. R67

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EU -