

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX XTREME Ceramic Spray Coating

Article number:

02571000, 02574000

UFI: 8U54-F0DK-Q00G-0JNT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Coating

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1A H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07

Signal word Warning

Hazard-determining components of labelling:

2-methylisothiazol-3(2H)-one

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing spray.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

(Contd. of page 1)

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** care emulsion**Dangerous components:**

CAS: 2682-20-4 EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	2-methylisothiazol-3(2H)-one ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	>0.0015-<0.01%
CAS: 3811-73-2 EINECS: 223-296-5 Reg.nr.: 01-2119493385-28-xxxx	pyridine-2-thiol 1-oxide, sodium salt ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	<0.01%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Remove soiled clothing**After inhalation:**

Supply fresh air.

No special measures required

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

sensitization

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

(Contd. of page 2)

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters
Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling No special precautions are necessary if used correctly.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls
Individual protection measures, such as personal protective equipment
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection: Not required in normal cases

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

Penetration time of glove material Value for the permeation: Level 6 (≥480min)
Eye/face protection Not required in normal cases

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	White
Odour:	Sweetish
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 °C (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not applicable
Upper:	Not applicable
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20 °C	6 - 7
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm²/s
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
Density and/or relative density	
Density at 20 °C:	0.99-1.01 g/cm³
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Emulsion
Important information on protection of health and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

(Contd. of page 4)

Desensitised explosives
Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid See Section 7 for information on safe handling.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards
Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:
CAS: 2682-20-4 2-methylisothiazol-3(2H)-one

EC 20 / 3h 2.8 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))

EC50/3h 34.6 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))

CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

LC50 / 96h 0.00767 mg/l (Zebraabärbling)

EC 20 / 3h 0.48 mg/l (KS) (OECD 209)

EC50/3h 1.81 mg/l (KS) (OECD 209)

EC50 / 48h 0.022 mg/l (daphnia)

EC50 / 72h 0.46 mg/l (Selenastrum capricornutum)

NOEC / 72 h 0.08 mg/l (Selenastrum capricornutum) (OECD 201)

12.2 Persistence and degradability
CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

Biodegradation >70 % (activated sludge) (OECD 301 B)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

(Contd. of page 5)

12.3 Bioaccumulative potential**CAS: 2682-20-4 2-methylisothiazol-3(2H)-one**

BCF	3.16
log Kow	≤0.32

CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

log Kow <-1.09 ((n-Octanol/Wasser) OECD 107)

12.4 Mobility in soil No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects**Additional ecological information:****General notes:** The product may not be released into the environment without control.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

- 1) Disposal / product
- 2) Disposal / contaminated packaging

07 06 99	wastes not otherwise specified
15 01 02	plastic packaging

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**

14.1 UN number or ID number	
ADR/RID/ADN, IMDG, IATA	Void

14.2 UN proper shipping name	
ADR/RID/ADN, IMDG, IATA	Void

14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG, IATA	
Class	Void

14.4 Packing group	
ADR/RID/ADN, IMDG, IATA	Void

14.5 Environmental hazards:	
Marine pollutant:	No

14.6 Special precautions for user	Not applicable.
--	-----------------

14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
---	-----------------

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating

(Contd. of page 6)

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
European Directives:

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--------------------	--

Date of previous version: 26.04.2022

Version number of previous version: 2.00

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

IOELV = indicative occupational exposure limit values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2023

Version: 2.01 (replaces version 2.00)

Revision: 25.07.2022

Trade name: SONAX XTREME Ceramic Spray Coating*Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**** Data compared to the previous version altered.**

(Contd. of page 7)

GB