

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

Article number: 02323000, 02325050, 02328050.01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC4 Anti-Freeze and de-icing products

PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate
vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Aqueous formulation of alcohol, glycol and tensides.

Dangerous components:

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	50 - <75%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-xxxx	ethanediol STOT RE 2, H373; Acute Tox. 4, H302	5 - <10%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

anionic surfactants	<5%
perfumes	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed Eye irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Fire-extinguishing powder

Alcohol resistant foam

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon dioxide (CO₂)

Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

Additional information

(Contd. of page 2)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:


Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:
Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:
CAS: 64-17-5 ethanol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

CAS: 107-21-1 ethanediol

WEL (Great Britain) Short-term value: 104** mg/m³, 40** ppm
Long-term value: 10* 52** mg/m³, 20** ppm
Sk *particulate **vapour

IOELV (EU) Short-term value: 104 mg/m³, 40 ppm
Long-term value: 52 mg/m³, 20 ppm
Skin

Regulatory information WEL (Great Britain): EH40/2011

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

(Contd. of page 3)

DNELs

CAS: 64-17-5 ethanol

Oral	DNEL	87 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	206 mg/kg bw/day (consumer) (long-term exposure - systemic effects) 343 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	950 mg/m ³ (consumer) (acute short-term exposure - local effects) 1,900 mg/m ³ (worker) (acute short-term exposure - local effects)
	DNEL	114 mg/m ³ (consumer) (long-term exposure - systemic effects) 950 mg/m ³ (worker) (long-term exposure - systemic effects)

CAS: 107-21-1 ethanediol

Dermal	DNEL	53 mg/kg bw/day (consumer) (long term (chronic) / systemic) 106 mg/kg bw/day (worker) (long term (chronic) / systemic)
Inhalative	DNEL	7 mg/m ³ (consumer) (long term (chronic) / local) 35 mg/m ³ (worker) (long term (chronic) / local)

PNECs

CAS: 64-17-5 ethanol

PNEC	0.96 mg/l (water (fresh water)) 0.79 mg/l (water (sea water))
PNEC	3.6 mg/kg (sediment (fresh water)) 2.9 mg/kg (sediment (sea water)) 0.63 mg/kg (soil)

CAS: 107-21-1 ethanediol

PNEC	199.5 mg/l (STP) 10 mg/l (water (intermittent release)) 10 mg/l (water (fresh water)) 1 mg/l (water (sea water))
PNEC	1.53 mg/kg (gro) 37 mg/kg (sediment (fresh water)) (dry weight) 3.7 mg/kg (sediment (sea water)) (dry weight)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Protection of hands: Not required in normal cases.

Eye protection:

Goggles recommended during refilling

[EN 166]

GB

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C:	5.5 - 6.5
--------------------	-----------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	78 - 200 °C

Flash point:	23 °C (EN ISO 1523)
--------------	---------------------

Flammability (solid, gas):	Not applicable.
----------------------------	-----------------

Decomposition temperature:	Not determined.
----------------------------	-----------------

Auto-ignition temperature:	Not determined.
----------------------------	-----------------

Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-----------------------	---

Explosion limits:

Lower:	3.5 Vol.% (Main ingredient data)
Upper:	15.0 Vol.% (Main ingredient data)

Vapour pressure:	Not determined.
------------------	-----------------

Density at 20 °C:	0.90 - 0.91 g/cm ³
-------------------	-------------------------------

Relative density	Not determined.
------------------	-----------------

Vapour density	Not determined.
----------------	-----------------

Evaporation rate	Not determined.
------------------	-----------------

Solubility in / Miscibility with water:

Fully miscible.

Partition coefficient: n-octanol/water:	Not determined.
---	-----------------

Viscosity:

Flow time at 20 °C	10 - 15 s (DIN EN ISO 2431/4mm)
--------------------	---------------------------------

Kinematic at 40 °C:	<20.5 mm ² /s
---------------------	--------------------------

9.2 Other information	No further relevant information available.
-----------------------	--

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 64-17-5 ethanol

Oral	LD50	5,560 mg/kg (guinea pig)
------	------	--------------------------

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

(Contd. of page 5)

		3,450 mg/kg (mouse)
		7,060 mg/kg (rat)
		6,300 mg/kg (rabbit)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4d	20,000 mg/l (rat)
CAS: 107-21-1 ethanediol		
Oral	LD50	7,712 mg/kg (rat)
Dermal	LD50	>3,500 mg/kg (mouse)
Inhalative	LC50 / 6 h	>2.5 mg/l (rat)

Primary irritant effect:
Skin corrosion/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Repeated dose toxicity
CAS: 64-17-5 ethanol

Oral	LOAEL	3,160 mg/kg (rat)
	NOAEL	1,730 mg/kg (rat)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:
CAS: 64-17-5 ethanol

LC50 / 48h	8,140 mg/l (Leuciscus idus)
LC50 / 24h	>100 mg/l (Daphnia magna)
EC5 / 16h	6,500 mg/l (Pseudomonas putida)
EC50 / 48h	9,268 mg/l (Daphnia magna)

CAS: 107-21-1 ethanediol

LC50 / 96h	72,860 mg/l (Pimephales promelas)
EC20 / 0.5 h	>1,995 mg/l (activated sludge)
EC50 / 48h	>100 mg/l (Daphnia magna)
EC50 / 96 h	6,500-13,000 mg/l (Pseudokirchneriella subcapitata)
NOEC / 7 d	8,590 mg/l (Ceriodaphnia Dubia) (EPA 600/4-89/001)
	15,380 mg/l (Pimephales promelas) (EPA 600/4-89/001)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

(Contd. of page 6)

12.3 Bioaccumulative potential

CAS: 107-21-1 ethanediol

log POW 1.36 log POW

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

20 01 29* detergents containing dangerous substances

Uncleaned packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

Recommendation:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

Recommended cleansing agents: Water

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1170

14.2 UN proper shipping name

ADR

IMDG, IATA

1170 ETHANOL SOLUTION

ETHANOL SOLUTION

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Transport category

3

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 5.01

Revision: 11.02.2019

Trade name: SONAX Xtreme Antifreeze + Clearview Concentrate

(Contd. of page 7)

Tunnel restriction code

D/E

UN "Model Regulation":

UN 1170 ETHANOL SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids

On basis of test data

Serious eye damage/eye irritation

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.