

SAFETY DATA SHEET CAR GOD CHROME POLISH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CAR GOD CHROME POLISH

Product number GOD102

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL EUROPE

79 rue du chemin vert

59.273 Fretin

TEL: 03 20 28 06 30 qualite@tetrosyl-france.com

Manufacturer TETROSYL LIMITED

Bury

Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981 (24 hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.

CAR GOD CHROME POLISH

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P261 Avoid breathing vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Contains 1,2-benzisothiazol-3(2H)-one, 2-METHYLISOTHIAZOL-3(2H)-ONE

Supplementary precautionary

P272 Contaminated work clothing should not be allowed out of the workplace.

statements P321 Specific treatment (see medical advice on this label).

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ALUMINIUM OXIDE 30-<60%

CAS number: 1344-28-1 EC number: 215-691-6

Classification
Not Classified

HYDROCARBONS C10-13 N-ALKANES, ISOALKANES,

10-<30%

CYCLICS < 2% AROMATICS

CAS number: — EC number: 918-481-9

Classification

Asp. Tox. 1 - H304

AMMONIA ...100% 0.3-<0.5%

CAS number: 1336-21-6 EC number: 215-647-6

M factor (Acute) = 1

Classification

Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400

SODIUM HYDROXIDE -<0.05

CAS number: 1310-73-2 EC number: 215-185-5

Classification

Met. Corr. 1 - H290 Skin Corr. 1A - H314 Eye Dam. 1 - H318

CAR GOD CHROME POLISH

2-METHYLISOTHIAZOL-3(2H)-ONE

-<0.05

CAS number: 2682-20-4 EC number: 220-239-6

M factor (Acute) = 10 M factor (Chronic) = 1

Corrosive to the respiratory tract.

May cause an allergic skin reaction. This substance has specific concentration limits.≥0.0015

Classification

Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 2 - H330 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1A - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

1,2-benzisothiazol-3(2H)-one

-<0.05

CAS number: 2634-33-5 EC number: 220-120-9

M factor (Acute) = 1

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Remove affected person from source of

contamination. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Move affected person to fresh

air at once. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a

large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any

discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

CAR GOD CHROME POLISH

Inhalation May cause an asthma-like shortness of breath. Vapours may cause drowsiness and

dizziness.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea,

headache, dizziness and intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon

dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours. Provide adequate ventilation. In case of spills, beware of slippery

floors and surfaces. For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination. Do not discharge into

drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in

Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and

seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

CAR GOD CHROME POLISH

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Read and follow manufacturer's recommendations. Do not handle broken

packages without protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ALUMINIUM OXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

AMMONIA ...100%

Long-term exposure limit (8-hour TWA): WEL 18 mg/m³ Short-term exposure limit (15-minute): WEL 25 mg/m³

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³ WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Provide eyewash

station.

Hygiene measures

Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated. Wash hands after contact. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

CAR GOD CHROME POLISH

9.1. Information on basic physical and chemical properties

Appearance Paste. Colour White.

Odour Ammonia.

Odour threshold Not determined. pΗ Not determined. Melting point Not determined.

>100°C @ 1013 hPa Initial boiling point and range

62°C Flash point

Evaporation rate Not determined. Upper/lower flammability or Not determined.

explosive limits

Vapour pressure Not determined.

Not determined. Vapour density

Relative density 1.285g/cm3 @ 20°C

Solubility(ies) Emulsible in water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Not determined. **Decomposition Temperature**

Viscosity >30000 cP @ 20°C

Oxidising properties Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product. Reactivity

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stability

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

CAR GOD CHROME POLISH

Hazardous decomposition

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

products other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Based on available data the classification criteria are not met. Summary

Petroleum Distillates Notes (oral LD50)

Acute toxicity - dermal

Based on available data the classification criteria are not met. Summary

Acute toxicity - inhalation

Based on available data the classification criteria are not met. Summary

Skin corrosion/irritation

Summary Based on available data the classification criteria are not met.

Serious eye damage/irritation

Based on available data the classification criteria are not met. Summary

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Based on available data the classification criteria are not met. Summary

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met. Summary

Specific target organ toxicity - single exposure

Based on available data the classification criteria are not met. Summary

Specific target organ toxicity - repeated exposure

Summary Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met. Summary

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion May cause discomfort if swallowed.

Skin contact May cause an allergic skin reaction. Prolonged and frequent contact may cause redness and

irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health

This chemical can be hazardous when inhaled and/or touched. This product may cause skin hazards

and eye irritation. Vapour from this product may be hazardous by inhalation.

Route of exposure Inhalation Ingestion. Skin and/or eye contact Skin absorption

CAR GOD CHROME POLISH

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does

not exclude the possibility that large or frequent spills can have a harmful or damaging effect

on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Petroleum Distillates

Not determined.

LC₅₀, 96 hours: 2 - 5mg/l mg/l, Fish

Acute toxicity - aquatic

invertebrates Petroleum Distillates

EC₅₀, 48 hours: 1.4mg/l mg/l, Daphnia magna

Acute toxicity - aquatic plants Petroleum Distillates

IC₅₀, 72 hours: 1 - 3mg/l mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsConfirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

CAR GOD CHROME POLISH

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Regulatory Department

Revision date 11/04/2022

Revision 5

Supersedes date 26/01/2022

SDS number 34303

SDS status Approved.

Hazard statements in full H290 May be corrosive to metals.

H301 Toxic if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.