

TEROSON VR 200

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 15

SDS No.: 485228 V003.0

Revision: 21.10.2022

printing date: 30.10.2023

Replaces version from: 19.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON VR 200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: disinfectants

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Chronic hazards to the aquatic environment H412 Harmful to aquatic life with long lasting effects.

Category 3

2.2. Label elements

Label elements (CLP):

Hazard statement: H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.

Prevention

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration ≥ the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	1-<= 5 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
C12-16 Alkyldimethylbenzylammonium chloride 68424-85-1 939-253-5 01-2119965180-41	0,1- <= 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 4, Oral, H302	M acute = 10 M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available. Declaration of ingredients according to Detergent Regulation 648/2004/EC

< 5 % cationic surfactants non-ionic surfactants

Allergenic fragrance Terpinolene, Camphor, Menthol ingredients >=100 ppm:

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in sealed original container.

Store in a cool, well-ventilated place.

7.3. Specific end use(s)

disinfectants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list	
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	200		Time Weighted Average (TWA):		IR_OEL	
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL	
Propan-2-ol 67-63-0 IISOPROPYL ALCOHOLI	400		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL	

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
		Perrou	mg/l	ppm	mg/kg	others	
Propan-2-ol	aqua		140,9 mg/l	•			
67-63-0	(freshwater)						
Propan-2-ol	aqua (marine		140,9 mg/l				
67-63-0	water)		1				
Propan-2-ol	sediment				552 mg/kg		
67-63-0	(freshwater)						
Propan-2-ol	sediment				552 mg/kg		
67-63-0	(marine water)		1		20 1		
Propan-2-ol	Soil				28 mg/kg		
67-63-0			140.0/1				
Propan-2-ol 67-63-0	aqua (intermittent		140,9 mg/l				
67-63-0	releases)						
Propan-2-ol	sewage		2251 mg/l				
67-63-0	treatment plant						
	(STP)						
Propan-2-ol	oral				160 mg/kg		
67-63-0							
Quaternary ammonium compounds, benzyl-	aqua		0,0009				
C12-16-alkyldimethyl, chlorides	(freshwater)		mg/l				
68424-85-1			0.00000				
Quaternary ammonium compounds, benzyl-	aqua (marine		0,00009				
C12-16-alkyldimethyl, chlorides 68424-85-1	water)		mg/l				
Quaternary ammonium compounds, benzyl-	aqua		0.00016				
C12-16-alkyldimethyl, chlorides	(intermittent		mg/l				
68424-85-1	releases)		IIIg/I				
Quaternary ammonium compounds, benzyl-	sewage		0,4 mg/l				
C12-16-alkyldimethyl, chlorides	treatment plant		3,1 8, -				
68424-85-1	(STP)						
Quaternary ammonium compounds, benzyl-	sediment				12,27		
C12-16-alkyldimethyl, chlorides	(freshwater)				mg/kg		
68424-85-1							
Quaternary ammonium compounds, benzyl-	sediment				13,09		
C12-16-alkyldimethyl, chlorides	(marine water)				mg/kg		
68424-85-1			1				
Quaternary ammonium compounds, benzyl-	Soil				7 mg/kg		
C12-16-alkyldimethyl, chlorides							
68424-85-1							

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m3	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
Quaternary ammonium compounds, benzyl- C12-16-alkyldimethyl, chlorides 68424-85-1	Workers	inhalation	Long term exposure - systemic effects		3,96 mg/m3	
Quaternary ammonium compounds, benzyl- C12-16-alkyldimethyl, chlorides 68424-85-1	Workers	dermal	Long term exposure - systemic effects		5,7 mg/kg	
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides 68424-85-1	General population	inhalation	Long term exposure - systemic effects		1,64 mg/m3	
Quaternary ammonium compounds, benzyl- C12-16-alkyldimethyl, chlorides 68424-85-1	General population	dermal	Long term exposure - systemic effects		3,4 mg/kg	
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides 68424-85-1	General population	oral	Long term exposure - systemic effects		3,4 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid Delivery form liquid

 $\begin{array}{ccc} \text{Colour} & \text{clear, colourless} \\ \text{Odor} & \text{Alcoholic} \\ \text{Melting point} & -10 \,^{\circ}\text{C} \, (14 \,^{\circ}\text{F}) \\ \text{Initial boiling point} & > 100 \,^{\circ}\text{C} \, (> 212 \,^{\circ}\text{F}) \\ \end{array}$

Flammability Currently under determination Explosive limits Currently under determination

Flash point up to 100°C. Aqueous preparation.

Auto-ignition temperature Currently under determination
Decomposition temperature Currently under determination

oH 6,7 - 7,3

(20 °C (68 °F))

Viscosity (kinematic) Currently under determination

Solubility (qualitative) fully miscible

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable

Mixture 2,1 hPa

Vapour pressure (20 °C (68 °F))

Density 0,930 - 1,03 g/cm3 no method

(20 °C (68 °F))

Relative vapour density: Currently under determination

Particle characteristics Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Propan-2-ol	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
67-63-0				Toxicity)
C12-16	LD50	344 mg/kg	rat	not specified
Alkyldimethylbenzylamm				
onium chloride				
68424-85-1				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Propan-2-ol	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
67-63-0				
C12-16	LD50	2.848 mg/kg	rat	not specified
Alkyldimethylbenzylamm				
onium chloride				
68424-85-1				

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	corrosive	4 h	rabbit	not specified

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
		ume		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Propan-2-ol	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
67-63-0				Irritation / Corrosion)
C12-16	Category 1		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
Alkyldimethylbenzylamm	(irreversible			
onium chloride	effects on the			
68424-85-1	eve)			

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
C12-16 Alkyldimethylbenzylamm onium chloride 68424-85-1	not carcinogenic	oral: feed	2 y daily	rat	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
Propan-2-ol	NOAEL P 853 mg/kg	One	oral:	rat	equivalent or similar to
67-63-0		generation	drinking		OECD Guideline 415 (One-
		study	water		Generation Reproduction
		-			Toxicity Study)
Propan-2-ol	NOAEL P 500 mg/kg	Two	oral: gavage	rat	equivalent or similar to
67-63-0		generation			OECD Guideline 416 (Two-
	NOAEL F1 1.000 mg/kg	study			Generation Reproduction
					Toxicity Study)
C12-16	NOAEL P 31 mg/kg	Two	oral: feed	rat	OECD Guideline 416 (Two-
Alkyldimethylbenzylamm		generation			Generation Reproduction
onium chloride	NOAEL F1 48 mg/kg	study			Toxicity Study)
68424-85-1					
	NOAEL F2 48 mg/kg				
	1				

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
Propan-2-ol		inhalation:	at least 104 w	rat	OECD Guideline 451
67-63-0		vapour	6 h/d, 5 d/w		(Carcinogenicity Studies)
C12-16	NOAEL 31 mg/kg	oral: feed	95 d	rat	OECD Guideline 408
Alkyldimethylbenzylamm			daily		(Repeated Dose 90-Day
onium chloride					Oral Toxicity in Rodents)
68424-85-1					

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Propan-2-ol 67-63-0	1,8 mm2/s	40 °C	ASTM Standard D7042	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

The biodegradability of the surfactants contained in the product is in accordance with the requirements of the EU Detergent Regulation (EC/648/2004).

The surfactants contained in the products are primary biodegradable to at least 90% on average.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Propan-2-ol	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish,
67-63-0					Acute Toxicity Test)
C12-16	LC50	0,28 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for
Alkyldimethylbenzylammoniu					Acute Toxicity Tests with
m chloride					Fish, Macroinvertebrates
68424-85-1					and Amphibians)
C12-16	NOEC	0,032 mg/l	34 d	Pimephales promelas	EPA OTS 797.1000 (Fish
Alkyldimethylbenzylammoniu					Early-life Stage Toxicity
m chloride					Test)
68424-85-1					

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
C12-16	EC50	0,016 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute
Alkyldimethylbenzylammoniu					Toxicity for Daphnia)
m chloride					
68424-85-1					

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Propan-2-ol	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
67-63-0					magna, Reproduction Test)
C12-16	NOEC	0,0042 mg/l	21 d	Daphnia magna	EPA OPP 72-4 (Fish Early
Alkyldimethylbenzylammoniu					Life-Stage/Aquatic
m chloride					Invert.Life-Cyclcle Studies)
68424-85-1					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
· I · ·	EC50	> 1.000 mg/l	96 h	1 `	OECD Guideline 201 (Alga,
67-63-0				name: Desmodesmus subspicatus)	Growth Inhibition Test)
Propan-2-ol	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new	OECD Guideline 201 (Alga,
67-63-0				name: Desmodesmus	Growth Inhibition Test)
				subspicatus)	
C12-16	EC50	0,049 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
Alkyldimethylbenzylammoniu					Growth Inhibition Test)
m chloride					
68424-85-1					
C12-16	EC10	0,009 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
Alkyldimethylbenzylammoniu					Growth Inhibition Test)
m chloride					
68424-85-1					

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Propan-2-ol	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209
67-63-0					(Activated Sludge,
					Respiration Inhibition Test)
C12-16	EC50	7,75 mg/l	3 h	activated sludge of a	OECD Guideline 209
Alkyldimethylbenzylammoniu				predominantly domestic sewage	(Activated Sludge,
m chloride					Respiration Inhibition Test)
68424-85-1					

12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
C12-16 Alkyldimethylbenzylammoniu m chloride 68424-85-1	readily biodegradable	aerobic	95,5 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
C12-16	79	35 d		Perca fluviatilis	not specified
Alkyldimethylbenzylammoniu					
m chloride					
68424-85-1					

12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Propan-2-ol	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
67-63-0			Flask Method)
C12-16	2,75		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
Alkyldimethylbenzylammoniu			Flask Method)
m chloride			
68424-85-1			

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Propan-2-ol	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
67-63-0	Bioaccumulative (vPvB) criteria.
C12-16 Alkyldimethylbenzylammonium	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
chloride	Bioaccumulative (vPvB) criteria.
68424-85-1	

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

EWC/EAK 070608

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

Not applicable

Not applicable

Not applicable

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):
Persistent organic pollutants (Regulation (EU) 2019/1021):
VOC content 1,3 %

(2010/75/EU)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

EU EXPLD 1:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.