

Page 1 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Felgen-Reiniger sauer 11 kg
Art.: 8192

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaner

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC35 - Washing and cleaning products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

PROC19 - Manual activities involving hand contact

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany

Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Corr.	1B	H314-Causes severe skin burns and eye damage.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 06.03.2019 / 0010

Replacing version dated / version: 23.05.2017 / 0009

Valid from: 06.03.2019

PDF print date: 06.03.2019

Felgen-Reiniger sauer 11 kg

Art.: 8192

STOT SE	3	H335-May cause respiratory irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Met. Corr.	1	H290-May be corrosive to metals.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H314-Causes severe skin burns and eye damage. H335-May cause respiratory irritation. H290-May be corrosive to metals.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves / protective clothing and eye protection / face protection.

P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P390-Absorb spillage to prevent material damage.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Hydrochloric acid

Isotridecanol, ethoxylated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrochloric acid	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	017-002-01-X
EINECS, ELINCS, NLP	231-595-7
CAS	7647-01-0
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Corr. 1B, H314 STOT SE 3, H335 Eye Dam. 1, H318

Isotridecanol, ethoxylated

Page 3 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	931-138-8 (REACH-IT List-No.)
CAS	69011-36-5
content %	5-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.
 Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
 Protect uninjured eye.
 Consult medical specialist.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 The following may occur:

Corrosive burns on skin as well as mucous membrane possible.
 Necrosis
 Risk of serious damage to eyes.
 Danger of blindness
 Ingestion:
 Pain in the mouth and throat
 Oesophageal perforation
 Gastric perforation

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

There should be an eyewash station and safety shower located near the area of use.
 Indications for the physician:
 Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

Oxides of carbon
Hydrogen chloride
Toxic pyrolysis products.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Neutralising is possible (only from a specialist).
Diluting with water is possible.
Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid inhalation of the vapours.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Do not use acid sensitive materials.
Acid-resistant floor necessary.
Do not store with alkalis.
Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

8.1 Control parameters

Chemical Name	Hydrochloric acid	Content %:10- <25
WEL-TWA: HCl 1 ppm (2 mg/m ³) (gas and aerosol mists) (WEL), 5 ppm (8 mg/m ³) (EU)	WEL-STEL: HCl 5 ppm (8 mg/m ³) (gas and aerosol mists) (WEL), 10 ppm (15 mg/m ³) (EU)	---
Monitoring procedures:		
- Compur - KITA-173 SA (548 980) - Compur - KITA-173 SB (548 998) - Draeger - Hydrochloric Acid 0,2/a (81 03 481) - Draeger - Hydrochloric Acid 1/a (CH 29 501) - Draeger - Hydrochloric Acid 50/a (67 28 181) - DFG (D), DFG (E) (Volatile inorganic acids) - 1998 - EU project - BC/CEN/ENTR/000/2002-16 card 93-1 (2004) - MTA/MA-019/A90 (Determination of inorganic acid anions in air) - OSHA ID-174SG (Hydrogen chloride in workplace atmospheresw) - 1986 - NIOSH 7903 (Acids, inorganic) - 1994		
BMGV: ---		Other information: ---

Hydrochloric acid						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	36	µg/l	
	Environment - marine		PNEC	36	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	45	µg/l	
	Environment - sewage treatment plant		PNEC	36	µg/l	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	15	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	8	mg/m ³	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. BS EN 14042.
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.

Page 6 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).
 If applicable
 Face protection (EN 166)

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN 374).
 Recommended
 Protective gloves in butyl rubber (EN 374).
 Minimum layer thickness in mm:
 0,5
 Permeation time (penetration time) in minutes:
 >480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Filter E-P2 (EN 14387)
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	0
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	n.a.
Upper explosive limit:	n.a.
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,09 g/ml (20°C)
Bulk density:	Not determined

Page 7 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

Solubility(ies):	Not determined
Water solubility:	Mixable
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.

10.5 Incompatible materials

See also section 7.
Avoid contact with strong alkalis (exothermic reaction possible).
Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).
Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Felgen-Reiniger sauer 11 kg Art.: 8192						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Corrosive
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

Page 8 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrochloric acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	900	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	> 5010	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit		Skin Corr. 1B
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No
Symptoms:						respiratory distress, unconsciousness, coughing, cramps, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						May cause respiratory irritation.

Isotridecanol, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>300-2000	mg/kg	Rat		References
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		References
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Intensively irritant, References
Respiratory or skin sensitisation:				Guinea pig		Negative, References
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, References
Reproductive toxicity:	NOAEL	>250	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	References
Aspiration hazard:						n.a.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	50	mg/kg bw/d	Rat		Target organ(s): heart, Target organ(s): liver, Target organ(s): kidneys, References

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Felgen-Reiniger sauer 11 kg Art.: 8192							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.

[illegible]

Page 10 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	-------------------------------------

Isotridecanol, ethoxylated							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	10-100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	1 - 10	mg/l	Cyprinus caprio	OECD 203 (Fish, Acute Toxicity Test)	References
12.1. Toxicity to daphnia:	EC50	48h	>1-10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	References
12.1. Toxicity to algae:	EC50	72h	10-100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	>10-100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	>1-10	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	References
12.2. Persistence and degradability:		28d	>70	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	References
12.2. Persistence and degradability:		28d	>60	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	References
12.4. Mobility in soil:	Kow		>5000				Adsorption in ground.
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50		>10000	mg/l	Pseudomonas putida	ISO 10712	
Toxicity to annelids:	LC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 01 aqueous washing liquids and mother liquors
20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 1789

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1789 HYDROCHLORIC ACID, SOLUTION

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Classification code:

C1

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

HYDROCHLORIC ACID SOLUTION

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

EmS:

F-A, S-B

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Hydrochloric acid solution

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

n.a.

REGULATION (EC) No 648/2004

5 % or over but less than 15 %

non-ionic surfactants

perfumes

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 06.03.2019 / 0010
Replacing version dated / version: 23.05.2017 / 0009
Valid from: 06.03.2019
PDF print date: 06.03.2019
Felgen-Reiniger sauer 11 kg
Art.: 8192

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 15, 16
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Corr. 1B, H314	Classification based on test data.
STOT SE 3, H335	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification based on test data.
Met. Corr. 1, H290	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Skin Corr. — Skin corrosion
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Eye Dam. — Serious eye damage
Met. Corr. — Substance or mixture corrosive to metals
Acute Tox. — Acute toxicity - oral

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

Page 13 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic

Page 14 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 06.03.2019 / 0010
 Replacing version dated / version: 23.05.2017 / 0009
 Valid from: 06.03.2019
 PDF print date: 06.03.2019
 Felgen-Reiniger sauer 11 kg
 Art.: 8192

PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.