

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

Article number:

03102000

UFI: M2V0-M06E-3003-6X4K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC34 Textile dyes, and impregnating products

Application of the substance / the mixture Impregnation spray for textiles

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS09

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 1)

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Formulation consisting of pressurised gas and solvents with additives**Dangerous components:**

EC No 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H336	3-<5%
EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; ⚠ Aquatic Chronic 3, H412	3-<5%
EC No 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Alternative CAS numbers: 90622-57-4, 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	1-<3%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	1-<3%

Additional information:**Hydrocarbon mixture:**

Benzene content < 0.1%

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 2)

After swallowing: Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Drowsiness

Reddening, drying and crack formation of the skin

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water spray

For safety reasons unsuitable extinguishing agents: Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 3)

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

WEL (Great Britain) Long-term value: 308 mg/m³, 50 ppm
Sk
IOELV (EU) Long-term value: 308 mg/m³, 50 ppm
Skin

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

DNELs

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	DNEL	699 mg/kg bw/day (consumer) (longterm systematic effects)
Dermal	DNEL	699 mg/kg bw/day (consumer) (longterm systematic effects)
	DNEL	773 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	2,035 mg/m ³ (worker) (longterm systematic effects)
	DNEL	608 mg/m ³ (consumer) (longterm systematic effects)

CAS: 67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg (consumer) (chronic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d))
		888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m ³ (consumer) (chronic effects)
		500 mg/m ³ (worker) (chronic effects)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 4)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
Dermal	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
		300 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)
Inhalative	DNEL	900 mg/m ³ (consumer) (ChronicExposure, SystemicEffects)
		1,500 mg/m ³ (worker) (ChronicExposure, SystemicEffects)

PNECs**CAS: 67-63-0 propan-2-ol**

PNEC	140.9 mg/l (sporadic release)
	2,251 mg/l (STP)
	140.9 mg/l (water (fresh water))
	140.9 mg/l (water (sea water))
PNEC	28 mg/kg (gro)
	552 mg/kg (sediment)

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Protection of hands: Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye protection:

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Aerosol
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 5)

Initial boiling point and boiling range: 82 - 165 °C (Active ingredient data)	
Flash point:	<10 °C (Active ingredient data)
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	0.7 Vol.% (Main ingredient data) 1,5 Vol.% (Propellant data)
Upper:	7.7 Vol.% (Main ingredient data) 10,9 Vol.% (Propellant data)
Vapour pressure:	Not determined.
Density at 20 °C:	0.75 - 0.76 g/cm ³ (DIN 51757) (Active ingredient data)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Kinematic at 40 °C:	<20.5 mm ² /s (Active ingredient data)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,800 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>23.3 mg/l (Ratte) (OECD 403)

CAS: 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
------	------	-------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 6)

Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4d	>4,951 mg/l (rat) (OECD 403)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5,000 mg/m ³ (rat) (OECD 403)
Hydrocarbons, C11-C13, isoalkanes,, <2% aromatics		
Oral	LD50	10,000 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (rabbit)

Primary irritant effect:
Skin corrosion/irritation

Based on available data, the classification criteria are not met.
Long-term exposure causes slight irritation of the skin.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.
May cause slight, short-term eye complaints.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

LL50 / 96h	>13.4 mg/l (Regenbogenforelle)
EL50 / 48h	3 mg/l (Daphnia magna)
EL50 / 72h	10-30 mg/l (Grünalge Pseudokirchneriella subcapitata)
NOELR 72 h	10 mg/l (Grünalge Pseudokirchneriella subcapitata)

CAS: 106-97-8 butane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

CAS: 74-98-6 propane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

CAS: 67-63-0 propan-2-ol

LC50 / 96h	9,640 mg/l (Pimephales promelas)
------------	----------------------------------

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 7)

LC50 / 24h	9,714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

LL50 / 96h	>10-<30 mg/l (Oncorhynchus mykiss)
EL50 / 48h	>22-<46 mg/l (Daphnia magna)
EL50 / 72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR 72 h	<1 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
NOEC/NOEL	0.011 mg/l (Daphnia magna) (21d)
NOELR 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR 21d	≥1 mg/l (Daphnia magna)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

CAS: 75-28-5 isobutane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

12.2 Persistence and degradability**CAS: 67-63-0 propan-2-ol**

Biodegradation 53 %

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation 89 % (28d)

12.3 Bioaccumulative potential No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** The product may not be released into the environment without control.**12.5 Results of PBT and vPvB assessment** Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 8)

14.3 Transport hazard class(es)

ADR



Class	2	5F Gases.
Label	2.1	

IMDG, IATA



Class	2.1
Label	2.1

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant:	Yes absent due to package size =<5l
--------------------------	--

14.6 Special precautions for user	see Sections 6-8 Warning: Gases.
--	-------------------------------------

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
--	-----------------

Transport/Additional information:

ADR

Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D

UN "Model Regulation":	UN1950, AEROSOLS, 2.1
-------------------------------	-----------------------

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 10)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 2.03

Revision: 25.08.2020

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 9)

H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

vPvB: very persistent and very bioaccumulative
PBT: persistent, bioaccumulative, toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
NOEL = No Observed Effect Level
NOEC = No Observed Effect Concentration
LC = Lethal Concentration
EC50 = half maximal effective concentration
log POW = Octanol / water partition coefficient
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ATE: acute toxicity estimate
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
IOELV = indicative occupational exposure limit values
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Version history and indication of changes: Replaces version 2.02.

*** Data compared to the previous version altered.**