

Printing date 28.10.2020 Version: 4.00 Revision: 16 11 2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Rust Converter & Primer

Article number: 311200

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the mixture Rust Converter

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements P102

Keep out of reach of children.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Copolymer dissolved in water

Dangerous components:

CAS: 111-76-2 2-butoxyethanol

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

(Contd. on page 2)

< 5%



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

(Contd. of page 1)

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling No special precautions are necessary if used correctly. **Information about fire - and explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 111-76-2 2-butoxyethanol

WEL (Great Britain) Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

(Contd. on page 3)



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

			(Contd. of pa
IOELV (EU)		Short-term value: 246 mg/m³, 50 ppm	
		Long-term value: 98 mg/m³, 20 ppm	
		Skin	
DNELs			
CAS: 111	-76-2 2-	butoxyethanol	
Oral	DNEL	13.4 mg/kg (consumer) (acute effect)	
		3.2 mg/kg (consumer) (chronic effect (24h))	
Dermal	DNEL	44.5 mg/kg (consumer) (acute effects (24h))	
		38 mg/kg (consumer) (chronic effect (24h))	
		89 mg/kg (worker) (acute effect (24h))	
		75 mg/kg (worker) (chronic effects (24h))	
Inhalative	DNEL	426 mg/m³ (consumer) (acute effects)	
		123 mg/m³ (consumer) (acute effect, local effects)	
		49 mg/m³ (consumer) (chronic effect)	
		663 mg/m³ (worker) (acute Effect)	
		246 mg/m³ (worker) (acute effect, local effects)	
		98 mg/m³ (worker) (chronic effects)	

CAS: 111-76-2 2-butoxyethanol

PNEC 2.8 mg/kg (gro)

8.14 mg/kg (sediment (fresh water)) 8.8 mg/l (water (fresh water)) 8.8 mg/l (water (sea water))

Ingredients with biological limit values:

CAS: 111-76-2 2-butoxyethanol

BMGV (Great Britain) 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace. Protection of hands: Not required in normal cases. Eye protection: Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid Colour: White Odour: Characteristic

(Contd. on page 4)



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

	(Co	ontd. of pa
Odour threshold:	Not determined.	
pH-value at 20 °C:	3.0 - 4.0 (DIN 19268)	
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : ≥100 °C	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits: Lower: Upper:	Not determined. Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C: Relative density Vapour density Evaporation rate	1.08 - 1.15 g/cm³ (DIN 51757) Not determined. Not determined. Not determined.	
Solubility in / Miscibility with water:	Easily soluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity: Flow time Dynamic: Kinematic: VOC (EC)	Not determined. Not determined. Not determined. 0.00 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid See Section 7 for information on safe handling.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture. **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50	values rel	levant for classification:					
CAS: 140	1-55-4 Tai	55-4 Tannins					
Oral	LD50	2260 mg/kg (rat)					
CAS: 111	76-2 2-bu	itoxyethanol					
Oral	LD50	1746 mg/kg (rat)					
Dermal	LD50	2270 mg/kg (rabbit)					
Inhalative	LC50/4h	2 - 20 mg/l (rat)					

(Contd. on page 5)



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

(Contd. of page 4)

Primary irritant effect:

Skin corrosion/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Serious eye damage/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

ſ	Aqua	atic toxicity:			
ſ	CAS	CAS: 111-76-2 2-butoxyethanol			
ſ	Oral	EC0/16h	700 mg/l (Pseudomonas putida)		
		EC0/168h	900 mg/l (scenedesmus quadricauda) (Zellvemehrungshemmtest)		
		EC50 / 24h	1720 mg/l (Daphnia magna)		
		LC 50 / 96 h	1490 mg/l (Lepomis macrochirus)		

12.2 Persistence and degradability

CAS: 111-76-2 2-butoxyethanol

Biodegradiation 100 % (OECD 301C)

12.3 Bioaccumulative potential

CAS: 111-76-2 2-butoxyethanol

log Kow 0.81 log Kow ([25°C (OECD 107)])

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

1) Disposal / product

2) Disposal / contaminated packaging

08 01 99 wastes not otherwise specified

15 01 02 plastic packaging

GB



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

(Contd. of page 5)

14.1 UN-Number		
ADR, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

EC/1907/2006 (REACh) EC/1272/2008 (CLP) EC/648/2004 VOC (2004/42/EC)

II / Bc:

(VOC max:540g/l) VOC: 22g/l

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Abbreviations and acronyms:

NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 7)



Printing date 28.10.2020 Version: 4.00 Revision: 16.11.2017

Trade name: SONAX Rust Converter & Primer

(Contd. of page 6)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
IOELV = indicative occupational exposure limit values
Acute Tox. 4: Acute toxicity - oral – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
* Data compared to the previous version altered.