

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Professional Tacky Lube Spray

Article number: 802300, 802400

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC24 Lubricants, greases, release products

Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + ++49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and solvents with additives

Dangerous components:

CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-50%
EC No 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	15-25%
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	15-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 5%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	< 5%
CAS: 4259-15-8 EINECS: 224-235-5 Reg.nr.: 01-2119493635-27-xxxx	2-ethylhexyl zinc dithiophosphate ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411	<1.0%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	<1.0%

Additional information:

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Nausea
Drowsiness
Skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam
Fire-extinguishing powder
Carbon dioxide
Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
Do not enter the hazardous area without a self-contained breathing apparatus.
See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
Do not allow to penetrate the ground/soil.
Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 3)

Do not spray onto a naked flame or any incandescent material.
Highly volatile, flammable constituents are released during processing.
Fumes can combine with air to form an explosive mixture.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

CAS: 110-54-3 n-hexane

WEL (Great Britain) Long-term value: 72 mg/m³, 20 ppm
IOELV (EU) Long-term value: 72 mg/m³, 20 ppm

DNELs

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	DNEL	149 mg/kg bw/day (consumer) (chronic exposure)
Dermal	DNEL	149 mg/kg bw/day (consumer) (chronic exposure)
		300 mg/kg bw/day (worker) (chronic exposure)
Inhalative	DNEL	477 mg/m ³ (consumer) (chronic exposure)
		2085 mg/m ³ (worker) (chronic exposure)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)
Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)
		773 mg/kg bw/day (worker) (chronic exposition / systemic effects)
Inhalative	DNEL	608 mg/m ³ (consumer) (chronic exposition / systemic effects)
		2035 mg/m ³ (worker) (chronic exposition / systemic effects)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 4)

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye protection:

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Aerosol
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.

Important information on protection of health and environment, and on safety.

data of the content without propellant

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>60 °C

Flash point: -24 °C

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air mixture.

Explosion limits:

Lower:	0.6 Vol %
Upper:	7.2 Vol %

Vapour pressure: Not determined.

Density at 20 °C: $0.79 - 0.80$ g/cm³ (DIN 51757)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Flow time	Not determined.
Dynamic:	Not determined.
Kinematic:	Not determined.

9.2 Other information

No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 5)

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	LD50	5500 mg/kg (rat)
Dermal	LD50	2770 mg/kg (rat)
Inhalative	LC50/4h	23.3 mg/l (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat) (OECD 401)
Dermal	LD50	>2920 mg/kg (rat) (OECD 402)
Inhalative	LC50/4h	25.2 mg/l (rat) (OECD 403)

CAS: 4259-15-8 2-ethylhexyl zinc dithiophosphate

Oral	LD50	3100 mg/kg (rat)
Dermal	LD50	5001 mg/kg (rat)

CAS: 110-54-3 n-hexane

Oral	LD50	28.7 mg/kg (rat)
Dermal	LD50	3295 mg/kg (rabbit)
Inhalative	LC50	97469 ppm (rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) Contains n-hexane!

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EC50 / 48h	>1 - 10 mg/l (Daphnia magna)
ErC 50 72h	>10 - 100 mg/l (algae)
LC 50 / 96 h	>1 - 10 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EL50 / 48h	3 mg/l (Daphnia magna) (OECD 202)
EL50 / 72h	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 / 96h	11.4 mg/l (Oncorhynchus mykiss) (OECD 203)
LOEC	0.32 mg/l (Daphnia magna)
NOEC / 21d	0.17 mg/l (Daphnia magna)
NOELR 72 h	3 mg/l (Pseudokirchneriella subcapitata)

CAS: 4259-15-8 2-ethylhexyl zinc dithiophosphate

EC50 / 48h	1.1 mg/l (daphnia)
ErC 50 72h	240 mg/l (Pseudomonas putida)
LC 50	1.1 mg/l (Oncorhynchus mykiss)

12.2 Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Biodegradation	81 % (28d)
----------------	------------

12.3 Bioaccumulative potential

CAS: 110-54-3 n-hexane

log POW	3.9 log POW
---------	-------------

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

15 01 10*	packaging containing residues of or contaminated by dangerous substances
-----------	--

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA	UN1950
-----------------	--------

14.2 UN proper shipping name

ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 7)

14.3 Transport hazard class(es)

ADR



Class	2	5F Gases.
Label	2.1	

IMDG, IATA



Class	2.1
Label	2.1

14.4 Packing group

ADR, IMDG, IATA	Void
-----------------	------

14.5 Environmental hazards:

Marine pollutant:	Yes absent due to package size =<5l
-------------------	--

14.6 Special precautions for user	Warning: Gases.
-----------------------------------	-----------------

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
---	-----------------

Transport/Additional information:

ADR

Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D

UN "Model Regulation":	UN1950, AEROSOLS, 2.1
------------------------	-----------------------

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics: CAS 92045-53-9

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane: CAS 64742-49-0

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Tacky Lube Spray

(Contd. of page 8)

Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

NOEL = No Observed Effect Level
NOEC = No Observed Effect Concentration
LC = Lethal Concentration
EC50 = half maximal effective concentration
log POW = Octanol / water partition coefficient
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ATE: acute toxicity estimate
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
IOELV = indicative occupational exposure limit values
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* **Data compared to the previous version altered.**

GB