

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX PROFESSIONAL Power Ice Rust Dissolver**Article number:** 829400**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC24 Lubricants, greases, release products**Application of the substance / the mixture**

Penetrating oil

Anticorrosion additive

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + 49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

Signal word Danger**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

GB

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and mineral oil with additives in petroleum distillate

Dangerous components:

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304	25 - <50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	20 - <25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	20 - <25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	5 - <10%
CAS: 72623-86-0 EINECS: 276-737-9 Reg.nr.: 01-2119474878-16-XXXX	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ⚠ Asp. Tox. 1, H304	3 - <5%

Additional information:

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Nausea

Drowsiness

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 2)

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

DNELs

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Inhalative	DNEL	1.2 mg/m ³ (consumer) (local / longterm (repeated)) 5.4 mg/m ³ (worker) (local / longterm (repeated))
------------	------	--

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Protection of hands: Not required in normal cases.

Eye protection: Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Aerosol
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined.

Important information on protection of health and environment, and on safety.

data of the content without propellant

pH-value: Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	180 - 270 °C

Flash point: 81 °C (DIN 51755)

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

(Contd. on page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 4)

Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined. In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	Explosion limits components: 0,6Vol% (Main ingredient data)
Upper:	Explosion limits components: 7,0Vol.% (Main ingredient data)
Vapour pressure:	Not determined.
Density at 20 °C:	0.81 - 0.82 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Flow time at 20 °C	10 - 15 s (DIN EN ISO 2431/4mm)
Dynamic:	Not determined.
Kinematic at 40 °C:	< 7 mm ² /s (DIN 51562)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5000 mg/m ³ (rat) (OECD 403)

CAS: 106-97-8 butane

Inhalative	LC50/4h	658 mg/l (rat)
------------	---------	----------------

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4h	>5000 mg/l (rat)

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 5)

Primary irritant effect:

Skin corrosion/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Serious eye damage/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Repeated dose toxicity

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

NOEC / 72 h >100 mg/l (algae)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

ELO 48 h 1000 mg/l (Daphnia magna)

ELO 72 h 1000 mg/l (Pseudokirchneriella subcapitata)

LLO 96 h 1000 mg/l (Oncorhynchus mykiss)

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

EC50 / 48h >100 mg/l (Crustacea)

ErC 50 / 72h >100 mg/l (algae)

LC 50 / 96 h >100 mg/l (fish)

12.2 Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation 69 % (28d)

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Biodegradation 53 % (28d)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver
European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

(Contd. of page 6)

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name
ADR
IMDG
IATA

1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

14.3 Transport hazard class(es)
ADR

Class
Label

2 5F Gases.
2.1

IMDG, IATA

Class
Label

2.1
2.1

14.4 Packing group
ADR, IMDG, IATA

Void

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user

see Sections 6-8
Warning: Gases.

Hazard identification number (Kemler code):

-

14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

Transport/Additional information:
ADR
Limited quantities (LQ)

1L

Transport category

2

Tunnel restriction code

D

UN "Model Regulation":

UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics: CAS 64742-47-8

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.10.2020

Version: 5.00

Revision: 10.10.2017

Trade name: SONAX PROFESSIONAL Power Ice Rust Dissolver

(Contd. of page 7)

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:
Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

Classification according to Regulation (EC) No 1272/2008

Aerosols On basis of test data

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Asp. Tox. 1: Aspiration hazard – Category 1

* **Data compared to the previous version altered.**